



POWERING
PERFORMANCE

PRODUCT DATA SHEET

Eurol Coolant XL -36°C

Long-life coolant, based on organic corrosion inhibitors

Article number E504140 Version 2.0 16/04/2025

Produktinformationen

Eurol Coolant XL -36°C is a long-life coolant based on mono-ethylene glycol and organic acid technology (OAT technology). Since Eurol Coolant XL -36°C meets the performance level of a wide range of specifications, it can be used in a variety of vehicles.

This coolant is to be used undiluted, so never top up with water. The product's lifespan is 5 years or 650,000 km for trucks or 250,000 km for passenger cars, whichever comes first.

Eurol Coolant XL -36°C is a modern coolant for water-cooled combustion engines and protects the system from freezing down to -36°C.

This coolant is free of nitrites, amines, borates, phosphates, nitrates, and silicates, contributing to a cleaner environment. Eurol Coolant XL -36°C prevents scale formation and offers excellent protection against cavitation. Additionally, it protects metal parts in the cooling system from corrosion. This coolant is completely safe for rubber, plastics, metals, or their alloys in cooling systems.

Always follow the manufacturer's instructions regarding the application of the correct coolant.

Performance level

- AFNOR NFR 15-601
- ASTM D3306
- ASTM D4656
- ASTM D4985
- BS 6580
- Case New Holland MAT3624
- DAF 74002
- DTFR 29D110 (MB 326.3)
- Ford WSS-M97B44-D
- GM 6277M
- JASO M325
- John Deere JDM H5
- Komatsu 07.892
- Liebherr MD1-36-130
- MAN 324 Typ SNF
- MTU MTL 5048
- Renault Type D
- SAE J1034
- STJLR 651.5003
- VW TL-774 D (G12)
- VW TL-774 F (G12+)

Recommended for use

- Volvo VCS

Physical properties

Characteristic	Value/Result	ASTM Standard
Color	Yellow	
Density at 20°C	1.07 kg/l	ASTM D 4052
Flash point	111 °C	ASTM D 92
Frost protection	-36.0 °C	ASTM D 1177
pH	8.4	

Eurol B.V., Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 88 250 22 00, info@eurol.com, eurol.com

This document is intended to inform you about the product features and possible applications of Eurol products. The information in this document is subject to change at any time without prior notice due to ongoing product research and development. The analysis data in this sheet contains typical values. Minor deviations, which can occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet has been compiled with great care, Eurol accepts no liability for damages resulting from any incompleteness and/or inaccuracies in the text. We always advise you to follow the manufacturer's instructions. The translations provided here are made using ChatGPT, an AI language model developed by OpenAI. While we strive to deliver accurate and useful translations, we cannot guarantee that all translations are error-free or always capture the correct context and nuances.