



Coolants & screenwash - Cooling fluids

Eurol Coolant XL-NM -36°C

Longlife coolant, containing nitrite, meeting ASTM 6210

Description

Eurol Coolant XL-NM -36 is coolant, based on mono-ethylene-glycol and organic corrosion inhibitors (silicate-free, with nitrite).

Eurol Coolant XL-NM -36 prevents from scale formation and offers an excellent protection against cavitation. Moreover, it protects metal parts in the cooling system against corrosion.

Eurol Coolant XL-NM -36 is amine, borate, phosphate, nitrate and silicate-free and in this way, contributes to a cleaner environment.

Eurol Coolant XL-NM -36 is completely safe for rubber, plastics, metals and aluminium or its alloys.

Eurol Coolant XL-NM -36 is a modern coolant for water-cooled combustion engines and protects the system from freezing up to -36 °C.

Eurol Coolant XL-NM -36 is diluted with water, so ready to use.

Performance level

- ASTM D6210
- ASTM D3306 / D4656 / D4985

Recommended for use

- CES 14603
- Caterpillar EC-1

Physical properties

Colour	red	
Density at 20°C	1.071 kg/l	ASTM D 4052
Flash point	111 °C	ASTM D 93
Frost protection	-36 °C	ASTM D 1177
pH	8.4	

Article number E504142
Version 1.0, 25-03-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.