



Coolants & screenwash - Cooling fluids

Eurol Coolant -36°C GLX

Silicate-free, long-life coolant TL-VW 774 F (G12+)

Description

Eurol Coolant -36 GLX is specially developed for the new generation cooling systems of modern car engines. Eurol Coolant -36 GLX, based on ethylene-glycol, has been approved by Volkswagen (TL 774 D) and meets the Renault D standard.

Eurol Coolant -36 GLX prevents scale forming and offers excellent protection against cavitation. Moreover, it protects all metals against corrosion, particularly aluminum and alloy irons, even at high temperatures.

Eurol Coolant -36 GLX protects against freezing up to -36 °C and contains environment-friendly additives (carboxyl-acids). This technology is known under the name OAT (Organic-Acid-Technology).

Eurol Coolant -36 GLX is to be used undiluted, so never top-up with pure water. Life-time of the product is 5 years or 650.000 kms for trucks or 250.000 kms for passenger cars, depending on which situation occurs first.

Eurol Coolant -36 GLX is nitrite, amine, borate, phosphate, nitrate and silicate free. The product is compatible with traditional coolants of traditional quality.

Performance level

- VW TL-774 F (G12+)
- VW TL-774 D (G12)
- BS 6580
- ASTM D3306
- ASTM D4985
- ASTM D4656
- Renault Type D
- NATO S-759
- JASO M325

Recommended for use

- Toyota TSK 2601G-8A

Physical properties

Colour	pink	
Density at 20°C	1.069 kg/l	ASTM D 4052
Flash point	111 °C	ASTM D 93
Frost protection	-36 °C	ASTM D 1177
pH	8.4	

Article number E504144
Version 2.0, 27-07-2023

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.