



Greases - Aerosols

Eurol Copper Grease Spray 400ML

Protects metal against seizure caused by corrosion and chemical attack

Description

Eurol Copper Grease Spray:

- is a multi-purpose sprayable grease with a wide temperature range that reduces wear on parts that are subjected to extreme pressure. To encounter pitting, thread deformation and galling due to corrosion and chemical exposure.
 - is formulated with a high quality bentonite grease with solid material copper.
 - is widely usable, and can be used for wheel nuts, exhaust, threads of spark plugs, bolts and nuts.
 - is not suitable for ABS and ASR brake systems
- Eurol Copper Grease Spray is water resistant and offers good resistance to high pressure. It also provides protection against corrosion and provides a good electrical conductivity.

Eurol Copper Grease Spray should be properly shaken before use.

Only use Eurol Copper Grease Spray in well-ventilated places.

Eurol Copper Grease Spray keeps for 3 years in an unopened can, when stored in a cool and dry place at temperatures between +5°C and +25°C.

Physical properties

Colour	Yellow
Flash point	-20 °C ASTM D 93

Article number E701130
Version 1.0, 16-02-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.