



POWERING
PERFORMANCE

Eurol Skala 05 Lube Spray 400ML

Lubricant for heavy loaded open gears

Article number E701170 Version 1.2 02/09/2025

Product information

Eurol Skala 05 Lube Spray is a high-quality industrial lubricant for heavily loaded bearings and open gears.

Eurol Skala 05 Lube Spray is free of bitumen and is extremely suitable for roller and sliding bearings.

The Zn-Technology developed by Eurol provides this lubricant with excellent anti-corrosion and water-repellent properties.

Shake the can well before each use, for at least 10 seconds. Spray from approximately 20 cm distance onto the object to be treated. Apply in the desired amount.

Use only outdoors or in a well-ventilated area. In case of contact with eyes, rinse immediately with plenty of water. Highly flammable.

Eurol Skala 05 Lube Spray has a shelf life of 3 years in a cool and dry place with a minimum temperature of +5°C and a maximum of +25°C.

Physical properties

Characteristic	Value/Result	ASTM Standard
Color	light brown	
Flash point	-95 °C	ASTM D 92

Eurol B.V., Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 88 250 22 00, info@eurol.com, eurol.com

This document is intended to inform you about the product features and possible applications of Eurol products. The information in this document is subject to change at any time without prior notice due to ongoing product research and development. The analysis data in this sheet contains typical values. Minor deviations, which can occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet has been compiled with great care, Eurol accepts no liability for damages resulting from any incompleteness and/or inaccuracies in the text. We always advise you to follow the manufacturer's instructions. The translations provided here are made using ChatGPT, an AI language model developed by OpenAI. While we strive to deliver accurate and useful translations, we cannot guarantee that all translations are error-free or always capture the correct context and nuances.