



Greases - Aerosols

# Eurol Skala 05 Lube Spray 400ML

Lubricant for heavy loaded open gears

## Description

Eurol Skala 05 Lube Spray is high quality industrial lubricant for highly loaded bearings and open gears.

Eurol Skala 05 Lube Spray is free of bitumen and is particularly suitable for roller and sliding bearings.

The by Eurol developed Zn-technology provides this lubricant excellent anti-corrosion and water repellent properties.

Eurol Skala 05 Lube Spray must be shaken well before use. Spray at approx. 20-25 cm from the object. Apply the desired quantity.

Use Eurol Skala 05 Lube Spray only in well ventilated areas. In case of eye contact immediately rinse eyes with plenty of water. Flammable substance.

Eurol Skala 05 Lube Spray has a shelf life of 3 years in an unopened container in a cool and dry place with a temperature range between +5°C and +25°C.

## Physical properties

Colour	Yellow
Flash point	-20 °C    ASTM D 93

Article number E701170  
Version 1.2, 16-03-2022

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.