



Technical fluids - Aerosols

Eurol ML Coating Spray 400ML

Description

Eurol ML Coating Spray is a spray that contains a low solvent wax which provides a good protection against corrosion.

Eurol ML Coating Spray has a good water repellent and penetrating properties. Eurol ML Coating Spray provides excellent protection against corrosion which makes it ideal for the inside of car doors, cavities in the vehicle and moving parts.

Eurol ML Coating Spray must be shaken well before use. Spray at approx. 20-25 cm from the object. Apply the desired quantity. The Product has to act for 5 to 10 minutes.

Spray only in well ventilated areas. In case of eye contact immediately rinse eyes with plenty of water. Flammable substance.

Eurol ML Coating Spray has a shelf life of 3 years in an unopened container in a cool and dry place with a temperature range between +5°C and +25°C.

Physical properties

Colour	Colourless	
Flash point	-20 °C	ASTM D 93

Article number E701390
Version 1.1, 18-06-2019

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.