



Additives - Oil

## Eurol Visco Oil Plus

Oil additive aimed at eliminating excessive oil consumption

### Description

Eurol Visco Oil Plus is an additive developed to increase the viscosity of oil in diesel or petrol engines, with or without turbocharger. It is part of a preventative maintenance procedure important to the health of old and high-mileage engines to be sure that you have maximum engine protection in areas where the summer temperatures are often in the range 35 - 50 °C.

Eurol Visco Oil Plus is recommended if your engine uses more than 1L of engine oil every 1.000km or you anticipate driving in extremely high temperatures during a holiday drive. Eurol Visco Oil Plus increases oil viscosity, creating a thicker lubricant film between moving parts.

After adding Eurol Visco Oil Plus to the engine oil, your vehicle runs smoothly with a diminished vibration when idling. It restores engine compression, improves shear stability under high temperature and high load, improves engine power and fuel economy. A 250ml bottle of Eurol Visco Oil Plus is recommended for use in 4L to 6L of engine oil by just adding the additive to the oil. Don't overfill your engine, the oil should mark full on dipstick. It will increase the viscosity up to 20%.

Eurol Visco Oil Plus is compatible with a wide range of engine oils (mineral or synthetic based). If the engine uses much more than 1L of engine oil every 500 km, it is recommended to take the car to a garage, where the professionals can locate the cause and repair it.

Users should consult the Material Safety Data Sheet of Eurol Visco Oil Plus for information about storage and shelf life. Please ask Eurol Research & Development if any further information is required.

### Physical properties

Colour	colourless to	
Density at 20°C	0.835 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	755 cSt	ASTM D 445
Viscosity, kinematic at 100°C	103 cSt	ASTM D 445
Viscosity Index	234	ASTM D 2270

Article number E802313  
Version 1.1, 12-03-2020

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, [www.eurol.com](http://www.eurol.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.