



Greases

Eurol Lithium Grease MPQ-2

Universal lithium grease for various applications

Description

Eurol Lithium Grease MPQ-2 (Multi Purpose Quality) is a high-quality stable grease, based on mineral oil and lithium soap as thickener. Due to the presence of additives and the strong adhesion to metals this grease has good anti-oxidant and corrosion preventing properties.

Eurol Lithium Grease MPQ-2 can be used up to 120°C, with peak temperatures up to 130°C. Furthermore, Eurol Lithium Grease MPQ-2 is suitable for high working loads, shock loads and where water and dirt may penetrate the greasing point.

Eurol Lithium Grease MPQ-2 guarantees optimal protection, also under heavy working conditions, extending equipment life-time and reducing maintenance costs.

Performance level

- DIN 51825: K2K-30

Physical properties

Colour	brown	
Viscosity, kinematic at 40°C	110 cSt	ASTM D 445
Viscosity, kinematic at 100°C	12 cSt	ASTM D 445
Flash point	150 °C	ASTM D 93
NLGI consistency	2	
Thickener type	Lithium	
Base oil type	Mineral	
Base oil viscosity	110 cSt	ASTM D 445
4-ball weld load	200 kg	ASTM D 2596
Operating temperature	-30 – 130 °C	

Article number E901039
Version 1.0, 13-12-2018

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.