



Greases

Eurol White Lithium Grease EP2

White multi-purpose grease with EP additives

Description

Eurol White Grease EP 2 has been especially developed for the lubrication of ball and roller bearings, working under conditions requiring EP additives.

Eurol White Grease EP 2 shows excellent oxidation stability and anti-wear properties.

Eurol White Grease EP 2 is water-repellent and offers good corrosion protection. Therefore, it is often used for sealing filters, chains and filter housings of cross motorcycles.

Because of the colour, Eurol White Grease EP 2 is pleasant to use. It prevents dirt of the object to be lubricated on to skin or clothing.

Performance level

- DIN 51825: K2K-30
- ISO-L-XCCEA2

Physical properties

Colour	white	
Density at 20°C	0.94 kg/l	ASTM D 4052
NLGI consistency	2	
Thickener type	Lithium	
Base oil type	Mineral	
Base oil viscosity	110 cSt	ASTM D 445
4-ball weld load	200 kg	ASTM D 2596
Operating temperature	-30 – 120 °C	
Dropping point	180 °C	

Article number E901080
Version 1.0, 16-02-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.