



Greases

Eurol Ceramic Grease

Universal assembly paste

Description

Eurol Ceramic Anti-Seize Paste has been especially formulated from high molecular oil, ceramic materials, and inorganic binder and additives.

Eurol Ceramic Anti-Seize Paste is a universal assembly paste with excellent lubricating properties and an excellent protection against scuffing. It offers long-lasting protection against corrosion and harmful external chemical reactions. The strong adherence prevents water wash off. Eurol Ceramic Anti-Seize Paste is used as an assembly paste for all parts and threaded components which are usually treated with metal containing pastes like bearings, chains, fittings, splines, brake parts and pneumatic appliances in garages and ship building, agricultural and industrial plants.

Eurol Ceramic Anti-Seize Paste should be applied as a thin layer on a clean and dry surface. Contamination with other greases has to be avoided.

Physical properties

Colour	white, Yellow	
Density at 20°C	1.1 kg/l	ASTM D 4052
Flash point	200 °C	ASTM D 93
NLGI consistency	2	
Thickener type	Bentone	
Base oil type	Mineral	
Operating temperature	-20 – 1200 °C	

Article number E901123
Version 1.0, 16-02-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.