



Eurol Ball Bearing Grease EP 2

Multi-Purpose grease for ball and roller bearings

Description

Eurol Ball Bearing Grease EP 2 has been especially developed for the lubrication of ball and roller bearings of motorcycles, mopeds and bicycles.

Eurol Ball Bearing Grease EP 2 is water-repellent and offers a good resistance against oxidation. Moreover, the product has excellent sealing capabilities and a good mechanical stability.

Eurol Ball Bearing Grease EP 2 is highly adhesive and reduces bearingwear to a minimum and protects all parts from corrosion.

Performance level

• DIN 51825: KP2K-30

• ISO-L-XCCIB 2

Physical properties

Colour	Yellow-brown	
Density at 20°C	0.94 kg/l	ASTM D 4052
NLGI consistency	2	
Thickener type	Lithium	
Base oil type	Mineral	
Base oil viscosity	110 cSt	ASTM D 445
4-ball weld load	260 kg	ASTM D 2596
Operating temperature	-30 – 120 °C	
Dropping point	180 °C	

Article number E901210 Version 1.0, 25-03-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturers instructions.