



Nautic line - Mineraal

Eurol Nautic L.10W-40 FCW

4 stroke oil for marine engines

Omschrijving

Eurol Nautic Line 10W-40 FCW is a motor oil that ensures an optimal lubrication and protection of 4 stroke in- and outboard marine engines requiring FC-W specification.

Eurol Nautic Line 10W-40 FCW fulfils the NMMA FCW requirements, such as protection against rust and corrosion through contact with (salt) water, a limited decrease in viscosity after long-term use and an excellent protection against wear and sedimentation, especially in case of fuel dilution*.

*Fuel dilution can happen in engines, when the motor runs for an extended time in neutral, and unburnt fuel leaks into the crankcase. Eurol Nautic Line 25W-40 FCW contains special additives that limit wear to a minimum both at low and high speeds.

Thanks to special additives, Eurol Nautic Line 10W-40 FCW will keep providing its high performance level even after the oil change term has passed. However, it is always best to ensure timely oil changes.

Prestatieniveau

- API SL
- JASO MA
- NMMA FC-W

Fysische eigenschappen

	bruin	
Kleur		
Dichtheid bij 20°C	0.858 kg/l	ASTM D 4052
Viscositeit, kinematisch bij 40°C	96.2 cSt	ASTM D 445
Viscositeit, kinematisch bij 100°C	14.8 cSt	ASTM D 445
Viscositeitsindex	161	ASTM D 2270
Viscositeit, dynamisch (CCS)	4509 cP	ASTM D 5293
Sulfaat	0.84 wt%	ASTM D 874
Vlampunt	204 °C	ASTM D 93
Pour point	-33 °C	ASTM D 97

Artikelnummer E100144
Versie 2.0, 05-10-2023

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Nederland, tel. +31 548 61 51 65, www.eurol.com

Dit document is bedoeld om u te informeren over producteigenschappen en mogelijke toepassingen van Eurol producten. De informatie in dit document kan altijd en zonder voorafgaand bericht gewijzigd worden door voortdurende productresearch en -ontwikkeling. De analysegegevens op dit blad bevatten typische waarden. Kleine afwijkingen, die kunnen voorkomen tijdens het normale vervaardigingsproces van het product, zullen de kwaliteit van het product niet beïnvloeden. Hoewel dit informatieblad met grote zorgvuldigheid is samengesteld, aanvaardt Eurol geen aansprakelijkheid voor schade als gevolg van onvolledigheden en/of onjuistheden in de tekst. Wij adviseren u altijd het voorschrift van de fabrikant te volgen.