

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 25-7-2023 Version: 1.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## **1.1. Product identifier**

Product form	: Mixture
Product name	: Eurol E-HD REEO
Product code	: E100310
Product group	: Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Intended for general public Main use category Use of the substance/mixture Function or use category

- : Industrial use,professional use,Consumer use
- : Lubricant
- : Lubricants and additives

#### 1.2.2. Uses advised against

No additional information available

## 1.3. Details of the supplier of the safety data sheet

Eurol B.V. Energiestraat 12 NL-7442 DA Nijverdal The Netherlands Tel: +31 548 615 165 reach@eurol.com - www.eurol.com

#### 1.4. Emergency telephone number

#### Emergency number

: For Transport Emergency Call +31 6 26 71 27 43 (24hr/day 7days/week)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital Msida MSD 2090 Msida	+356 2545 6508	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

## **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

### Not classified

## Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 2.2. Label elements Labelling according to Regulation (EC) No. 1272/2008 [CLP] Precautionary statements (CLP) : P102 - Keep out of reach of children. : EUH208 - Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs, EUH-statements calcium salts, Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated, 1-(N,N-bis(2ethylhexyl)aminomethyl)-1,2,4-triazole. May produce an allergic reaction. EUH210 - Safety data sheet available on request. Child-resistant fastening Not applicable : Tactile warning : Not applicable 2.3. Other hazards Other hazards not contributing to the classification : This product floats on water and may affect the oxygen-balance in the water. The base oil contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT classified as H350: May cause cancer" (Note L).". USED ENGINE OILS: Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## **SECTION 3: Composition/information on ingredients**

## 3.1. Substances

### Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Dec-1-ene, trimers, hydrogenated	CAS-No.: 157707-86-3 EC-No.: 500-393-3 REACH-no: 01-2119493949- 12	35 – 50	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.]	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627- 25	25 – 35	Asp. Tox. 1, H304
Highly refined mineral oil (C15 -C50) substance with a Community workplace exposure limit	REACH-no: 01-2119484627- 25; 01-2119487077-29: 01- 2119471299-27	3 – 5	Not classified
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert- butyl-4-hydroxyphenyl)propionate	CAS-No.: 125643-61-0 EC-No.: 406-040-9 EC Index-No.: 607-530-00-7 REACH-no: 01-0000015551- 76	1 – 3	Aquatic Chronic 4, H413

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating light vacuum gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of approximately 32cSt at 40 °C. It contains a relatively large proportion of saturated hydrocarbons.]	CAS-No.: 72623-87-1 EC-No.: 276-738-4 EC Index-No.: 649-483-00-5 REACH-no: 01-2119474889- 13	1-3	Asp. Tox. 1, H304
Benzenesulfonic acid, methyl-, mono-C20-24- branched alkyl derivs., calcium salts	CAS-No.: 722503-68-6 EC-No.: 682-816-2	0,1 – 1	Skin Sens. 1B, H317
Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated	EC-No.: 953-650-0 EC Index-No.: 953-650-0	0,1 – 1	Skin Sens. 1B, H317 Repr. 2, H361d
1-(N,N-bis(2-ethylhexyl)aminomethyl)-1,2,4-triazole	CAS-No.: 91273-04-0 EC-No.: 401-280-0 EC Index-No.: 613-072-00-9 REACH-no: 01-2119930450- 49	0,1 – 1	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general First-aid measures after inhalation First-aid measures after skin contact First-aid measures after eye contact First-aid measures after ingestion	<ul> <li>Seek medical attention if ill effect develops.</li> <li>Remove person to fresh air and keep comfortable for breathing.</li> <li>Wash skin with plenty of water.</li> <li>Rinse eyes with water as a precaution.</li> <li>Call a poison center or a doctor if you feel unwell.</li> </ul>
4.2. Most important symptoms and effects,	both acute and delayed
Symptoms/effects after inhalation	: At normal ambient temperatures this product will be unlikely to present an inhalation hazar because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
Symptoms/effects after skin contact	: Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis. High pressure injection of product into the skin may lead local necrosis if the product is not surgically removed.
Symptoms/effects after eye contact	: Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.
Symptoms/effects after ingestion	: Bad taste. Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea.
Symptoms/effects upon intravenous administration	: Unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Unsuitable extinguishing media	: Do not use a heavy water stream. Use of heavy stream of water may spread fire.
5.2. Special hazards arising from the subs	tance or mixture
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	<ul> <li>Combustion generates: CO, CO2, POx, NOx, SOx, H2S.</li> <li>Not expected to be a fire/explosion hazard under normal conditions of use.</li> <li>Toxic fumes may be released.</li> </ul>
5.3. Advice for firefighters	
Precautionary measures fire Firefighting instructions Protection during firefighting Other information	<ul> <li>Do not enter fire area without proper protective equipment, including respiratory protection.</li> <li>Use water spray or fog for cooling exposed containers.</li> <li>Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.</li> <li>Prevent fire fighting water from entering the environment. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.</li> </ul>

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective equip	ment and emergency procedures	
General measures	: Spill area may be slippery. Prevent soil and water pollution. Prevent entry to sewers and public waters.	
6.1.1. For non-emergency personnel		
Protective equipment	: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Use protective clothing.	
Emergency procedures	: Ventilate spillage area.	
6.1.2. For emergency responders		
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
Emergency procedures	: No specific measures are necessary.	
6.2. Environmental precautions		

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up		
For containment Methods for cleaning up Other information	<ul> <li>Large quantities: Contain large spillage with sand or earth.</li> <li>Take up liquid spill into absorbent material.</li> <li>Dispose of materials or solid residues at an authorized site.</li> </ul>	
6.4. Reference to other sections		

For further information refer to section 13.

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed	: Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.
Precautions for safe handling Hygiene measures	<ul> <li>Ensure good ventilation of the work station. Wear personal protective equipment.</li> <li>Do no eat, drink or smoke when using this product. Always wash hands after handling the product.</li> </ul>
7.2. Conditions for safe storage, inclu	ding any incompatibilities
Technical measures	: Keep container tightly closed and in well ventilated place.

25-7-2023 (Issue date)

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Storage conditions	: Store in a well-ventilated place. Keep cool.
Incompatible products	: Reacts vigorously with strong oxidizers and acids.
Maximum storage period	: 5 year
Storage temperature	: ≤ 40 °C
Information on mixed storage	: Keep away from : Oxidizing materials. Strong acids.
Storage area	: Store at ambient temperature.
Special rules on packaging	: Keep container tightly closed and dry.

7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

Highly refined mineral oil (C15 -C50)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOELV TWA (mg/m <sup>3</sup> ) 5 mg/m <sup>3</sup>	

#### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

Exposure-value for oil mist

: 10 mg/m3 (15 min.) or 5 mg/m3 (8 hours).

#### 8.1.5. Control banding

No additional information available

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Gloves. In case of splash hazard: safety glasses. Eye protection should only be necessary where liquid could be splashed or sprayed. **Personal protective equipment symbol(s):** 



#### 8.2.2.1. Eye and face protection

Eye protection: Safety glasses

#### 8.2.2.2. Skin protection

Skin and body protection: Wear suitable protective clothing

Hand protection: Protective gloves

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### Other skin protection

### Materials for protective clothing:

PVC gloves. Neoprene or nitrile rubber gloves

#### 8.2.2.3. Respiratory protection

#### **Respiratory protection:**

In case of insufficient ventilation, wear suitable respiratory equipment.

#### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

#### Consumer exposure controls:

PVC gloves. Neoprene or nitrile rubber gloves.

#### Other information:

Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: brown.
Appearance	: Oily. Liquid.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: -42 °C
Freezing point	: Not available
Boiling point	: > 280 °C
Flammability (solid, gas)	: Non flammable.
Explosive limits	: 0,6 – 7 vol %
Lower explosive limit (LEL)	: 0,6 vol %
Upper explosive limit (UEL)	: 7 vol %
Flash point	: > 210 °C
Auto-ignition temperature	: > 240 °C
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 50 – 75 mm²/s
Solubility	: insoluble in water.
Log Kow	: Not available
Log Pow	: > 3
Vapour Pressure 20°C	: < 0,1 hPa
Vapour pressure at 50°C	: Not available
Density	: 0,84 – 0,85 kg/l
Relative density	: Not available
Relative vapour density at 20°C	: > 1 (air=1)
Particle characteristics	Not applicable

#### 9.2. Other information

9.2.1. Information with regard to physical hazar	d classes
Explosion limits	: 0,6 – 7 vol %
9.2.2. Other safety characteristics	
Relative evaporation rate (butylacetate=1)	: < 0,1
VOC content	: 0 %
Other properties	: Gas/vapour heavier than air at 20°C

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

according to the REACH Regulation (EC) 1907/2006 amended	by Regulation (EU) 2020/878
SECTION 10: Stability and reactivity	
10.1. Reactivity	
Stable under normal conditions of use.	
10.2. Chemical stability	
Stable under normal conditions.	
10.3. Possibility of hazardous reactions	
Refer to section 10.1 on Reactivity.	
10.4. Conditions to avoid	
Moisture. Overheating.	
10.5. Incompatible materials	
Strong oxidizing agents. Strong acids.	
10.6. Hazardous decomposition products	
CO, CO2, POx, NOx, SOx, H2S.	
SECTION 11: Toxicological information	
11.1. Information on hazard classes as defined	d in Population (EC) No. 1272/2008
	Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) :	Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met)
reaction mass of isomers of: C7-9-alkyl 3-(3,5	-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
hydrocarbons obtained by treating light vacu hydrogen in the presence of a catalyst in a tw consists predominantly of hydrocarbons have	eated neutral oil-based; Baseoil— unspecified; [A complex combination of um gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with to stage process with dewaxing being carried out between the two stages. It ing carbon numbers predominantly in the range of C20 through C50 and proximately 32cSt at 40 °C. It contains a relatively large proportion of
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
obtained by treating a petroleum fraction with carbon numbers predominantly in the range of	araffinic; Baseoil— unspecified; [A complex combination of hydrocarbons hydrogen in the presence of a catalyst. It consists of hydrocarbons having of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F roportion of saturated hydrocarbons.] (64742-54-7)
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg

LD50 dermal rat	> 2000 mg/kg	
LC50 Inhalation - Rat	> 5,53 mg/l	
Dec-1-ene, trimers, hydrogenated (157707-86-3)		
LD50 oral rat	> 5000 mg/kg	

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dec-1-ene, trimers, hydrogenated (157707-86	-3)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat (Dust/Mist)	> 5,2 mg/l/4h
1-(N,N-bis(2-ethylhexyl)aminomethyl)-1,2,4-tr	iazole (91273-04-0)
LD50 oral rat	2356 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
ATE CLP (oral)	2356 mg/kg bodyweight
Skin corrosion/irritation :	Not classified
Serious eye damage/irritation :	Not classified
Respiratory or skin sensitisation :	Not classified
Germ cell mutagenicity :	Not classified
Carcinogenicity :	Not classified
Reproductive toxicity :	Not classified
1-(N,N-bis(2-ethylhexyl)aminomethyl)-1,2,4-tr	iazole (91273-04-0)
NOAEL (animal/male, F1)	100 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
STOT-single exposure :	Not classified
STOT-repeated exposure	Not classified
reaction mass of isomers of: C7-9-alkyl 3-(3,5	-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)
	The second se
NOAEL (oral, rat, 90 days)	5 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days) Lubricating oils (petroleum), C20-50, hydrotre hydrocarbons obtained by treating light vacu hydrogen in the presence of a catalyst in a tw consists predominantly of hydrocarbons hav	5 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents) eated neutral oil-based; Baseoil— unspecified; [A complex combination of num gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with
NOAEL (oral, rat, 90 days) Lubricating oils (petroleum), C20-50, hydrotre hydrocarbons obtained by treating light vacu hydrogen in the presence of a catalyst in a two consists predominantly of hydrocarbons hav produces a finished oil with a viscosity of app	5 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents) eated neutral oil-based; Baseoil— unspecified; [A complex combination of num gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with to stage process with dewaxing being carried out between the two stages. It ing carbon numbers predominantly in the range of C20 through C50 and
NOAEL (oral, rat, 90 days) Lubricating oils (petroleum), C20-50, hydrotre hydrocarbons obtained by treating light vacu hydrogen in the presence of a catalyst in a tw consists predominantly of hydrocarbons hav produces a finished oil with a viscosity of app saturated hydrocarbons.] (72623-87-1)	5 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents) eated neutral oil-based; Baseoil— unspecified; [A complex combination of num gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with yo stage process with dewaxing being carried out between the two stages. It ing carbon numbers predominantly in the range of C20 through C50 and proximately 32cSt at 40 °C. It contains a relatively large proportion of 125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408
NOAEL (oral, rat, 90 days) Lubricating oils (petroleum), C20-50, hydrotre hydrocarbons obtained by treating light vacu hydrogen in the presence of a catalyst in a tw consists predominantly of hydrocarbons hav produces a finished oil with a viscosity of app saturated hydrocarbons.] (72623-87-1) LOAEL (oral, rat, 90 days) NOAEC (inhalation, rat, dust/mist/fume, 90 days)	5 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)         eated neutral oil-based; Baseoil— unspecified; [A complex combination of num gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with the stage process with dewaxing being carried out between the two stages. It ing carbon numbers predominantly in the range of C20 through C50 and proximately 32cSt at 40 °C. It contains a relatively large proportion of         125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)         > 0,98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity:
NOAEL (oral, rat, 90 days) Lubricating oils (petroleum), C20-50, hydrotre hydrocarbons obtained by treating light vacu hydrogen in the presence of a catalyst in a tw consists predominantly of hydrocarbons hav produces a finished oil with a viscosity of app saturated hydrocarbons.] (72623-87-1) LOAEL (oral, rat, 90 days) NOAEC (inhalation, rat, dust/mist/fume, 90 days)	5 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)         eated neutral oil-based; Baseoil— unspecified; [A complex combination of num gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with vo stage process with dewaxing being carried out between the two stages. It ing carbon numbers predominantly in the range of C20 through C50 and proximately 32cSt at 40 °C. It contains a relatively large proportion of         125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)         > 0,98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
NOAEL (oral, rat, 90 days)         Lubricating oils (petroleum), C20-50, hydrotree hydrocarbons obtained by treating light vacue hydrogen in the presence of a catalyst in a two consists predominantly of hydrocarbons hav produces a finished oil with a viscosity of appeared and the hydrocarbons.] (72623-87-1)         LOAEL (oral, rat, 90 days)         NOAEC (inhalation, rat, dust/mist/fume, 90 days)         Aspiration hazard	5 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)         eated neutral oil-based; Baseoil— unspecified; [A complex combination of num gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with vo stage process with dewaxing being carried out between the two stages. It ing carbon numbers predominantly in the range of C20 through C50 and proximately 32cSt at 40 °C. It contains a relatively large proportion of         125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)         > 0,98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
NOAEL (oral, rat, 90 days)         Lubricating oils (petroleum), C20-50, hydrotree         hydrocarbons obtained by treating light vacue         hydrogen in the presence of a catalyst in a two         consists predominantly of hydrocarbons have         produces a finished oil with a viscosity of apperterm         saturated hydrocarbons.] (72623-87-1)         LOAEL (oral, rat, 90 days)         NOAEC (inhalation, rat, dust/mist/fume, 90 days)         Aspiration hazard         Eurol E-HD REEO         Viscosity, kinematic         Lubricating oils (petroleum), C20-50, hydrotree         hydrocarbons obtained by treating light vacue         hydrogen in the presence of a catalyst in a two         consists predominantly of hydrocarbons have	5 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)         eated neutral oil-based; Baseoil— unspecified; [A complex combination of tum gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with yo stage process with dewaxing being carried out between the two stages. It ing carbon numbers predominantly in the range of C20 through C50 and proximately 32cSt at 40 °C. It contains a relatively large proportion of         125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)         > 0,98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)         Not classified         50 – 75 mm²/s         eated neutral oil-based; Baseoil— unspecified; [A complex combination of num gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with
NOAEL (oral, rat, 90 days)         Lubricating oils (petroleum), C20-50, hydrotree         hydrocarbons obtained by treating light vacue         hydrogen in the presence of a catalyst in a two         consists predominantly of hydrocarbons have         produces a finished oil with a viscosity of apperterm         saturated hydrocarbons.] (72623-87-1)         LOAEL (oral, rat, 90 days)         NOAEC (inhalation, rat, dust/mist/fume, 90 days)         Aspiration hazard         Eurol E-HD REEO         Viscosity, kinematic         Lubricating oils (petroleum), C20-50, hydrotree         hydrogen in the presence of a catalyst in a two         consists predominantly of hydrocarbons have         produces a finished oil with a viscosity of apperterm	5 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)         Bated neutral oil-based; Baseoil— unspecified; [A complex combination of pum gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with yo stage process with dewaxing being carried out between the two stages. It ing carbon numbers predominantly in the range of C20 through C50 and proximately 32cSt at 40 °C. It contains a relatively large proportion of         125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)         > 0,98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)         Not classified         50 – 75 mm²/s         pated neutral oil-based; Baseoil— unspecified; [A complex combination of um gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with yo stage process with dewaxing being carried out between the two stages. It ing carbon numbers predominantly in the range of C20 through C50 and
NOAEL (oral, rat, 90 days)         Lubricating oils (petroleum), C20-50, hydrotree hydrocarbons obtained by treating light vacue hydrogen in the presence of a catalyst in a two consists predominantly of hydrocarbons hav produces a finished oil with a viscosity of appearaturated hydrocarbons.] (72623-87-1)         LOAEL (oral, rat, 90 days)         NOAEC (inhalation, rat, dust/mist/fume, 90 days)         Aspiration hazard         Eurol E-HD REEO         Viscosity, kinematic         Lubricating oils (petroleum), C20-50, hydrotree hydrocarbons obtained by treating light vacue hydrogen in the presence of a catalyst in a two consists predominantly of hydrocarbons hav produces a finished oil with a viscosity of appearaturated hydrocarbons.] (72623-87-1)	5 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)         eated neutral oil-based; Baseoil— unspecified; [A complex combination of num gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with the stage process with dewaxing being carried out between the two stages. It ing carbon numbers predominantly in the range of C20 through C50 and proximately 32cSt at 40 °C. It contains a relatively large proportion of         125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)         > 0,98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)         Not classified         50 – 75 mm²/s         eated neutral oil-based; Baseoil— unspecified; [A complex combination of num gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with to stage process with dewaxing being carried out between the two stages. It ing carbon numbers predominantly in the range of C20 through C50 and proximately 32cSt at 40 °C. It contains a relatively large proportion of         10000 – 12000 mm²/s
NOAEL (oral, rat, 90 days)         Lubricating oils (petroleum), C20-50, hydrotree hydrocarbons obtained by treating light vacue hydrogen in the presence of a catalyst in a two consists predominantly of hydrocarbons hav produces a finished oil with a viscosity of appearance of a catalyst in a two consists predominantly of hydrocarbons hav produces a finished oil with a viscosity of appearance of a catalyst in a two consists predominantly of hydrocarbons.] (72623-87-1)         LOAEL (oral, rat, 90 days)         NOAEC (inhalation, rat, dust/mist/fume, 90 days)         Aspiration hazard         Eurol E-HD REEO         Viscosity, kinematic         Lubricating oils (petroleum), C20-50, hydrotree hydrocarbons obtained by treating light vacue hydrogen in the presence of a catalyst in a two consists predominantly of hydrocarbons hav produces a finished oil with a viscosity of appearance of a catalyst in a two consists predominantly of hydrocarbons hav produces a finished oil with a viscosity of appearance of a catalyst in a two consists predominantly of hydrocarbons hav produces a finished oil with a viscosity of appearance of a catalyst in a two consists predominantly of hydrocarbons hav produces a finished oil with a viscosity of appearance of a catalyst in a two consists predominantly of hydrocarbons have produces a finished oil with a viscosity of appearance of a catalyst in a two consists predominantly of hydrocarbons hav produces a finished oil with a viscosity of appearance of a catalyst in a two consists predominantly of hydrocarbons hav produces a finished oil with a viscosity of appearance of a catalyst in a two consists predominantly of hydrocarbons hav produces a finished oil with a viscosity of appearance of a catalyst in a two consists predominantly of hydrocarbons hav produces a finished oil wit	5 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)         eated neutral oil-based; Baseoil— unspecified; [A complex combination of num gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with the stage process with dewaxing being carried out between the two stages. It ing carbon numbers predominantly in the range of C20 through C50 and proximately 32cSt at 40 °C. It contains a relatively large proportion of         125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)         > 0,98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)         Not classified         50 – 75 mm²/s         eated neutral oil-based; Baseoil— unspecified; [A complex combination of num gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with the stage process with dewaxing being carried out between the two stages. It ing carbon numbers predominantly in the range of C20 through C50 and proximately 32cSt at 40 °C. It contains a relatively large proportion of         10000 – 12000 mm²/s

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### **11.2. Information on other hazards**

#### 11.2.1. Endocrine disrupting properties

#### No additional information available

#### 11.2.2. Other information

Other information

: Toxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the toxicology of similar products, Likely route of exposure: ingestion, skin and eye.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Ecology - water	: This product floats on water and may affect the oxygen-balance in the water.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long–term (chronic)	: Not classified

reaction mass of isomers of: C7-9-alkyl 3-(3,5	-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)
LC50 fish 1	> 1000 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
LC50 fish 2	> 2 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 Daphnia 1	0,9 mg/l Test organisms (species): Daphnia magna
EC50 Daphnia 2	> 1000 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 3 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC (chronic)	≤ 0,01 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Highly refined mineral oil (C15 -C50)	

EC50 other aquatic organisms 1	1,2 mg/l
Distillates (petroleum), hydrotreated heavy pa	raffinic; Baseoil— unspecified; [A complex combination of hydrocarbons

obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

LC50 fish 1	100 mg/l	
EC50 Daphnia 1	10000 mg/l	
EC50 72h - Algae [1]	> 100 mg/l	
Dec-1-ene, trimers, hydrogenated (157707-86-3)		
LC50 fish 1	> 1000 mg/l Oncorhynchus mykiss (Rainbow trout)	
LC50 fish 2	> 750 mg/l Pimephales promelas	
EC50 Daphnia 1	190 mg/l EC50 48h - Daphnia magna [mg/l]	
EC50 72h - Algae [1] 1000 mg/l Scenedesmus capricornutum		
1-(N,N-bis(2-ethylhexyl)aminomethyl)-1,2,4-triazole (91273-04-0)		
LC50 fish 1	1,1 mg/l Test organisms (species): other:	
EC50 Daphnia 1	9,3 mg/l	

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1-(N,N-bis(2-ethylhexyl)aminomethyl)-1,2,4-tr	azole (91273-04-0)
EC50 72h - Algae [2]	> 0,96 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
NOEC chronic fish	> 100 mg/l Test organisms (species): Duration: '28 d'
12.2. Persistence and degradability	
Eurol E-HD REEO	
Persistence and degradability	Not readily biodegradable.
Dec-1-ene, trimers, hydrogenated (157707-86	-3)
Persistence and degradability	Not readily biodegradable.
12.3. Bioaccumulative potential	
Eurol E-HD REEO	
Log Pow	> 3
Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.
reaction mass of isomers of: C7-9-alkyl 3-(3,5	-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)
Bioconcentration factor (BCF REACH)	260 (OECD 305 method)
Log Pow	9,2
consists predominantly of hydrocarbons hav	ro stage process with dewaxing being carried out between the two stages. It ing carbon numbers predominantly in the range of C20 through C50 and proximately 32cSt at 40 °C. It contains a relatively large proportion of
Log Pow	> 6
Dec-1-ene, trimers, hydrogenated (157707-86	3)
Log Pow	> 10
Log Kow	> 6,5
Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.
1-(N,N-bis(2-ethylhexyl)aminomethyl)-1,2,4-tr	azole (91273-04-0)
Log Pow	5,3
12.4. Mobility in soil	
Eurol E-HD REEO	
Eurol E-HD REEO Ecology - soil	Not miscible with water. Spillages may penetrate the soil causing ground water contamination. This product floats on water and may affect the oxygen-balance in the water.
	contamination. This product floats on water and may affect the oxygen-balance in the water.
Ecology - soil	contamination. This product floats on water and may affect the oxygen-balance in the water.

No additional information available

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## 12.6. Endocrine disrupting properties

### No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal consideration	S
13.1. Waste treatment methods	
Regional legislation (waste) Product/Packaging disposal recommendations Waste disposal recommendations	<ul> <li>Disposal must be done according to official regulations.</li> <li>Dispose of contents/container in accordance with licensed collector's sorting instructions.</li> <li>Dispose in a safe manner in accordance with local/national regulations. Do not discharge into drains or the environment.</li> </ul>
Additional information Ecology - waste materials European List of Waste (LoW) code	<ul> <li>Hazardous waste.</li> <li>Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. When not empty dispose of this container at hazardous or special waste collection point.</li> <li>13 02 06* - Synthetic engine, gear and lubricating oils</li> </ul>

# **SECTION 14: Transport information**

### In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	ΙΑΤΑ	ADN	RID
14.1. UN number or ID n	umber	· · ·		
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping	g name	· · ·		
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard c	lass(es)	· · ·		
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group		· · ·		
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental haz	ards			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

14.6. Special precautions for user

# Overland transport

Not applicable

Transport by sea Not applicable

Air transport

Not applicable

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### Inland waterway transport

Not applicable

#### **Rail transport**

Not applicable

#### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

### **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

#### **REACH Annex XVII (Restriction List)**

#### **EU restriction list (REACH Annex XVII)**

Reference code	Applicable on
3(b)	Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts ; Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated ; Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating light vacuum gas oil, heavy vacuum gas oil and solvent deasphalted residual oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of approximately 32cSt at 40 °C. It contains a relatively large proportion of saturated hydrocarbons obtained by treating a petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] ; Dec-1-ene, trimers, hydrogenated ; 1-(N,N-bis(2- ethylhexyl)aminomethyl)-1,2,4-triazole
3(c)	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate ; 1-(N,N-bis(2- ethylhexyl)aminomethyl)-1,2,4-triazole

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

### VOC Directive (2004/42)

VOC content

: 0 %

## Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### **Drug Precursors Regulation (273/2004)**

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

No additional information available

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

# 15.2. Chemical safety assessment

A chemical safety assessment has been carried out

For the following substances of this mixture a chemical safety assessment has been carried out:

Dec-1-ene, trimers, hydrogenated

# **SECTION 16: Other information**

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
ΙΑΤΑ	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
L		

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Data sources

 REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
 None.

#### Other information

Full text of H- and EUH-statements:		
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4	
Asp. Tox. 1	Aspiration hazard, Category 1	
EUH208	Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs, calcium salts, Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated, 1-(N,N-bis(2-ethylhexyl)aminomethyl)-1,2,4-triazole. May produce an allergic reaction.	
EUH210	Safety data sheet available on request.	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
H304	May be fatal if swallowed and enters airways.	
H314	Causes severe skin burns and eye damage.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H361d	Suspected of damaging the unborn child.	
H411	Toxic to aquatic life with long lasting effects.	
H413	May cause long lasting harmful effects to aquatic life.	
Repr. 2	Reproductive toxicity, Category 2	
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B	
Skin Sens. 1	Skin sensitisation, Category 1	
Skin Sens. 1B	Skin sensitisation, category 1B	

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.