



# Eurol Hykrol VHLP ISO 15

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Issue date: 14.02.2014 Revision date: 20.06.2023 Supersedes: 03.04.2023 Version: 3.4

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : Eurol Hykrol VHLP ISO 15  
Product code : E108805  
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : Industrial use, professional use, Consumer use  
Use of the substance/mixture : Lubricant  
Function or use category : Lubricants and additives

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Eurol B.V.  
Energiestraat 12  
NL-7442 DA Nijverdal  
The Netherlands  
Tel: +31 548 615 165  
[reach@eurol.com](mailto:reach@eurol.com) - [www.eurol.com](http://www.eurol.com)

#### 1.4. Emergency telephone number

Emergency number : For Transport Emergency Call +31 6 26 71 27 43 (24hr/day 7days/week)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital Msida MSD 2090 Msida	+356 2545 6508	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aspiration hazard, Category 1 H304  
Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

May be fatal if swallowed and enters airways.

# Eurol Hykrol VHLP ISO 15

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS08

CLP Signal word :

Danger

Contains :

Distillates (petroleum), hydrotreated heavy paraffinic; Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %); Distillates (petroleum), hydrotreated light paraffinic  
H304 - May be fatal if swallowed and enters airways.

Hazard statements (CLP) :

P102 - Keep out of reach of children.

Precautionary statements (CLP) :

P301+P310+P331 - IF SWALLOWED: Immediately call a doctor. Do NOT induce vomiting.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Child-resistant fastening :

Applicable

Tactile warning :

Applicable

### 2.3. Other hazards

Other hazards not contributing to the classification : This product floats on water and may affect the oxygen-balance in the water. The base oil contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT classified as H350: May cause cancer" (Note L).".

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated light paraffinic	CAS-No.: 64742-55-8 EC-No.: 265-158-7 EC Index-No.: 649-468-00-3 REACH-no: 01-2119487077-29	$\geq 50$	Asp. Tox. 1, H304
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)	EC-No.: 920-360-0 REACH-no: 01-2119448343-41	3 – 5	Asp. Tox. 1, H304

# Eurol Hykrol VHLP ISO 15

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.]	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25	1 – 3	Asp. Tox. 1, H304
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate substance with national workplace exposure limit(s) (GB, IE, MT); substance with a Community workplace exposure limit	CAS-No.: 80-62-6 EC-No.: 201-297-1 EC Index-No.: 607-035-00-6 REACH-no: 01-2119452498-28	< 0,1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
Symptoms/effects after skin contact	: Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis. High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.
Symptoms/effects after eye contact	: Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.
Symptoms/effects after ingestion	: Risk of lung oedema.
Symptoms/effects upon intravenous administration	: Unknown.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Combustion generates: CO, CO <sub>2</sub> , PO <sub>x</sub> , NO <sub>x</sub> , SO <sub>x</sub> , H <sub>2</sub> S. Metal oxides.
Explosion hazard	: Not expected to be a fire/explosion hazard under normal conditions of use.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

### 5.3. Advice for firefighters

Precautionary measures fire	: Do not enter fire area without proper protective equipment, including respiratory protection.
-----------------------------	---

# Eurol Hykrol VHLP ISO 15

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Prevent fire fighting water from entering the environment. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Spill area may be slippery. Prevent soil and water pollution. Prevent entry to sewers and public waters.
------------------	--

#### 6.1.1. For non-emergency personnel

Protective equipment	: When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Use protective clothing.
Emergency procedures	: Ventilate spillage area.

#### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: No specific measures are necessary.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment	: Large quantities: Contain large spillage with sand or earth.
Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed	: Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.
Precautions for safe handling	: Ensure good ventilation of the work station. Wear personal protective equipment.
Hygiene measures	: Do no eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep container tightly closed and in well ventilated place.
Storage conditions	: Store locked up. Store in a well-ventilated place. Keep cool.
Incompatible products	: Reacts vigorously with strong oxidizers and acids.
Maximum storage period	: 5 year
Storage temperature	: ≤ 40 °C
Information on mixed storage	: Keep away from : Oxidizing materials. Strong acids.
Storage area	: Store at ambient temperature.
Special rules on packaging	: Keep container tightly closed and dry.

### 7.3. Specific end use(s)

No additional information available

# Eurol Hykrol VHLP ISO 15

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Methyl methacrylate
IOELV STEL (ppm)	100 ppm
Regulatory reference	COMMISSION DIRECTIVE 2009/161/EU
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Methyl methacrylate
OEL (8 hours ref) (ppm)	50 ppm
OEL (15 min ref) (ppm)	100 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values), Sens. (In the workplace respiratory or dermal exposures to sensitising agents may occur. Sensitizers may evoke respiratory or dermal reactions, e.g. asthma, rhinitis and allergic contact dermatitis. The notation does not distinguish between respiratory or dermal sensitisation. Chemical agents that are sensitizers present special problems in the workplace. Should an employee become sensitised, subsequent exposure may cause intense responses, even at low exposure concentrations well below the OELV. Exposure should be eliminated or significantly reduced through control measures such as engineering and process controls and use of personal protective equipment (PPE))
Regulatory reference	Chemical Agents Code of Practice 2021
<b>Malta - Occupational Exposure Limits</b>	
Local name	Methyl methacrylate
OEL TWA (ppm)	50 ppm
OEL STEL (ppm)	100 ppm
Regulatory reference	S.L.424.24 - Chemical Agents at Work Regulations (L.N.356 of 2021)
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	Methyl methacrylate
WEL TWA (mg/m <sup>3</sup> )	208 mg/m <sup>3</sup>
WEL TWA (ppm)	50 ppm
WEL STEL (mg/m <sup>3</sup> )	416 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	100 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

##### 8.1.2. Recommended monitoring procedures

No additional information available

##### 8.1.3. Air contaminants formed

No additional information available

##### 8.1.4. DNEL and PNEC

Exposure-value for oil mist : 10 mg/m<sup>3</sup> (15 min.) or 5 mg/m<sup>3</sup> (8 hours).

##### 8.1.5. Control banding

No additional information available

# Eurol Hykrol VHLP ISO 15

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

**Appropriate engineering controls:**

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

**Personal protective equipment:**

Gloves. In case of splash hazard: safety glasses. Eye protection should only be necessary where liquid could be splashed or sprayed.

**Personal protective equipment symbol(s):**



##### 8.2.2.1. Eye and face protection

**Eye protection:**

Safety glasses

##### 8.2.2.2. Skin protection

**Skin and body protection:**

Wear suitable protective clothing

**Hand protection:**

Protective gloves

**Other skin protection**

**Materials for protective clothing:**

PVC gloves. Neoprene or nitrile rubber gloves

##### 8.2.2.3. Respiratory protection

**Respiratory protection:**

In case of insufficient ventilation, wear suitable respiratory equipment.

##### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

**Environmental exposure controls:**

Avoid release to the environment.

**Consumer exposure controls:**

PVC gloves. Neoprene or nitrile rubber gloves.

**Other information:**

Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless_EIGA0755.
Appearance	: Oily. Liquid.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: ≤ -42 °C ASTM D 97
Freezing point	: Not available
Boiling point	: > 280 °C
Flammability (solid, gas)	: Non flammable.

# EuroI Hykrol VHLP ISO 15

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Lower explosive limit (LEL)	: 0,6 vol %
Upper explosive limit (UEL)	: 7 vol %
Flash point	: > 180 °C ASTM D92
Auto-ignition temperature	: > 240 °C
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 10 – 20 mm <sup>2</sup> /s at 40 °C, ASTM D 445
Solubility	: insoluble in water.
Log Kow	: Not available
Log Pow	: > 3
Vapour Pressure 20°C	: < 0,1 hPa
Vapour pressure at 50°C	: Not available
Density	: 0,83 – 0,84 kg/l ASTM D 4052
Relative density	: Not available
Relative vapour density at 20°C	: > 1 (air=1)
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

Explosion limits : 0,6 – 7 vol %

#### 9.2.2. Other safety characteristics

Relative evaporation rate (butylacetate=1) : < 0,1  
VOC content : 0 %  
Other properties : Gas/vapour heavier than air at 20°C

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Stable under normal conditions of use.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

### 10.4. Conditions to avoid

Moisture. Overheating.

### 10.5. Incompatible materials

Strong oxidizing agents. Strong acids.

### 10.6. Hazardous decomposition products

CO, CO<sub>2</sub>, PO<sub>x</sub>, NO<sub>x</sub>, SO<sub>x</sub>, H<sub>2</sub>S. Metal oxides.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 ml/kg

# Eurol Hykrol VHLP ISO 15

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)</b>	
LC50 Inhalation - Rat (Vapours)	29,8 mg/l/4h
<b>Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	> 5,53 mg/l
<b>Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)</b>	
LD50 oral rat	> 4150 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 1700 mg/kg
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5,28 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
<b>Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
<b>methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)</b>	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified
<b>methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)</b>	
NOAEL (oral, rat, 90 days)	2000 mg/kg bodyweight/day
NOAEC (inhalation, rat, vapour, 90 days)	25 mg/l
<b>Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)</b>	
NOAEL (dermal, rat/rabbit, 90 days)	> 495 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
<b>Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)</b>	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0,98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
Aspiration hazard	: May be fatal if swallowed and enters airways.
<b>Eurol Hykrol VHLP ISO 15</b>	
Viscosity, kinematic	10 – 20 mm <sup>2</sup> /s at 40 °C, ASTM D 445



# Eurol Hykrol VHLP ISO 15

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)</b>	
Viscosity, kinematic	1400 mm <sup>2</sup> /s ASTM D 445
<b>Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, aromatics (2-30 %)</b>	
Viscosity, kinematic	5,25 mm <sup>2</sup> /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm <sup>2</sup> /s)'

### 11.2. Information on other hazards

#### 11.2.1. Endocrine disrupting properties

No additional information available

#### 11.2.2. Other information

Other information : Toxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the toxicology of similar products, Likely route of exposure: ingestion, skin and eye.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Ecology - water : This product floats on water and may affect the oxygen-balance in the water.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

<b>methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)</b>	
LC50 fish 1	> 79 mg/l Oncorhynchus mykiss (Rainbow trout)
EC50 Daphnia 1	69 mg/l Daphnia magna (Water flea)
NOEC (chronic)	110 mg/l Selenastrum capricornutum
NOEC chronic fish	9,4 mg/l (OECD 210 method)
NOEC chronic crustacea	37 mg/l Daphnia magna (Water flea)

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)**

LC50 fish 1	100 mg/l
EC50 Daphnia 1	10000 mg/l
EC50 72h - Algae [1]	> 100 mg/l

### 12.2. Persistence and degradability

<b>Eurol Hykrol VHLP ISO 15</b>	
Persistence and degradability	Not readily biodegradable.
<b>methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)</b>	
Persistence and degradability	Readily biodegradable in water.
Biodegradation	94 % (OECD 301C method)

# EuroI Hykrol VHLP ISO 15

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.3. Bioaccumulative potential

#### EuroI Hykrol VHLP ISO 15

Log Pow	> 3
Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.

#### methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)

Log Kow	1,38
---------	------

### 12.4. Mobility in soil

#### EuroI Hykrol VHLP ISO 15

Ecology - soil	Not miscible with water. Spillages may penetrate the soil causing ground water contamination. This product floats on water and may affect the oxygen-balance in the water.
----------------	--

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Do not discharge into drains or the environment.
Additional information	: Hazardous waste.
Ecology - waste materials	: Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. When not empty dispose of this container at hazardous or special waste collection point.
European List of Waste (LoW, EC 2000/532)	: 13 01 10* - mineral based non-chlorinated hydraulic oils

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
Not regulated for transport				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

# EuroI Hykrol VHLP ISO 15

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
<b>14.3. Transport hazard class(es)</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

No data available

#### Transport by sea

No data available

#### Air transport

No data available

#### Inland waterway transport

No data available

#### Rail transport

No data available

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)	
Reference code	Applicable on
3(a)	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate
3(b)	EuroI Hykrol VHLP ISO 15 ; methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate ; Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.]
40.	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

# EuroI Hykrol VHLP ISO 15

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

### VOC Directive (2004/42)

VOC content : 0 %

### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

No additional information available

## 15.2. Chemical safety assessment

A chemical safety assessment has been carried out

## SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Supersedes	Modified	
	Revision date	Modified	
2.2	Precautionary statements (CLP)	Modified	

### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration

# EuroI Hykrol VHLP ISO 15

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:	
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Asp. Tox. 1	H304	Calculation method

Safety Data Sheet (SDS), EU

# **Eurol Hykrol VHLP ISO 15**

## **Safety Data Sheet**

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

---

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.