



Eurol HPG 80W-140 TDL GL4/5

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 26.05.2016 Revision date: 13.10.2023 Supersedes: 23.12.2022 Version: 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Eurol HPG 80W-140 TDL GL4/5
Product code : E110626
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Industrial use, professional use, Consumer use
Use of the substance/mixture : Lubricant
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Eurol B.V.
Energiestraat 12
NL-7442 DA Nijverdal
The Netherlands
Tel: +31 548 615 165
reach@eurol.com - www.eurol.com

1.4. Emergency telephone number

Emergency number : For Transport Emergency Call +31 6 26 71 27 43 (24hr/day 7days/week)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital Msida MSD 2090 Msida	+356 2545 6508	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

EuroI HPG 80W-140 TDL GL4/5

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements (CLP)	: P102 - Keep out of reach of children.
EUH-statements	: EUH208 - Contains Methyl methacrylate, Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl, Magnesium metaborate. May produce an allergic reaction. EUH210 - Safety data sheet available on request.
Child-resistant fastening	: Not applicable
Tactile warning	: Not applicable

2.3. Other hazards

Other hazards not contributing to the classification : This product floats on water and may affect the oxygen-balance in the water. The base oil contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT classified as H350: May cause cancer" (Note L).".

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.]	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25	35 – 50	Asp. Tox. 1, H304
Highly refined base oil substance with a Community workplace exposure limit	CAS-No.: 64741-88-4 EC-No.: 265-090-8 REACH-no: 01-2119488706-23	10 – 25	Not classified
Polysulfides, di-tert-Bu	CAS-No.: 68937-96-2 EC-No.: 273-103-3 REACH-no: 01-2119540515-43	3 – 5	Skin Sens. 1B, H317 Aquatic Chronic 3, H412
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl	EC-No.: 931-384-6 REACH-no: 01-2119493620-38	1 – 3	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Mineral Oil	-	1 – 3	Asp. Tox. 1, H304

EuroI HPG 80W-140 TDL GL4/5

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Magnesium metaborate	CAS-No.: 13703-82-7 EC-No.: 237-235-5 REACH-no: 01-2120769073-53	0,1 – 1	Skin Sens. 1, H317
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate substance with national workplace exposure limit(s) (GB, IE, MT); substance with a Community workplace exposure limit	CAS-No.: 80-62-6 EC-No.: 201-297-1 EC Index-No.: 607-035-00-6 REACH-no: 01-2119452498-28	0,1 – 1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335

Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
Polysulfides, di-tert-Bu	CAS-No.: 68937-96-2 EC-No.: 273-103-3 REACH-no: 01-2119540515-43	(45,9 ≤ C < 100) Skin Sens. 1B, H317
Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl	EC-No.: 931-384-6 REACH-no: 01-2119493620-38	(9,39 ≤ C < 100) Skin Sens. 1B, H317 (50 ≤ C < 100) Eye Dam. 1, H318 (50 ≤ C < 100) Eye Irrit. 2, H319
Magnesium metaborate	CAS-No.: 13703-82-7 EC-No.: 237-235-5 REACH-no: 01-2120769073-53	(15 ≤ C < 100) Skin Sens. 1B, H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Seek medical attention if ill effect develops.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
Symptoms/effects after skin contact	: Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis. High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.
Symptoms/effects after eye contact	: Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.
Symptoms/effects after ingestion	: Bad taste. Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea.
Symptoms/effects upon intravenous administration	: Unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

EuroI HPG 80W-140 TDL GL4/5

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Combustion generates: CO, CO₂, POx, NOx, SOx, H₂S.
Explosion hazard : Not expected to be a fire/explosion hazard under normal conditions of use.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

- Precautionary measures fire : Do not enter fire area without proper protective equipment, including respiratory protection.
Firefighting instructions : Use water spray or fog for cooling exposed containers.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information : Prevent fire fighting water from entering the environment. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Spill area may be slippery. Prevent soil and water pollution. Prevent entry to sewers and public waters.

6.1.1. For non-emergency personnel

- Protective equipment : When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Use protective clothing.
Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : No specific measures are necessary.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Large quantities: Contain large spillage with sand or earth.
Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.
Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.

EuroI HPG 80W-140 TDL GL4/5

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hygiene measures : Do no eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep container tightly closed and in well ventilated place.
Storage conditions : Store in a well-ventilated place. Keep cool.
Incompatible products : Reacts vigorously with strong oxidizers and acids.
Maximum storage period : 5 year
Storage temperature : ≤ 40 °C
Information on mixed storage : Keep away from : Oxidizing materials. Strong acids.
Storage area : Store at ambient temperature.
Special rules on packaging : Keep container tightly closed and dry.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Methyl methacrylate
IOELV STEL (ppm)	100 ppm
Regulatory reference	COMMISSION DIRECTIVE 2009/161/EU
Ireland - Occupational Exposure Limits	
Local name	Methyl methacrylate
OEL (8 hours ref) (ppm)	50 ppm
OEL (15 min ref) (ppm)	100 ppm
Remark	IOELV (Indicative Occupational Exposure Limit Values), Sens. (In the workplace respiratory or dermal exposures to sensitising agents may occur. Sensitizers may evoke respiratory or dermal reactions, e.g. asthma, rhinitis and allergic contact dermatitis. The notation does not distinguish between respiratory or dermal sensitisation. Chemical agents that are sensitizers present special problems in the workplace. Should an employee become sensitised, subsequent exposure may cause intense responses, even at low exposure concentrations well below the OELV. Exposure should be eliminated or significantly reduced through control measures such as engineering and process controls and use of personal protective equipment (PPE))
Regulatory reference	Chemical Agents Code of Practice 2021
Malta - Occupational Exposure Limits	
Local name	Methyl methacrylate
OEL TWA (ppm)	50 ppm
OEL STEL (ppm)	100 ppm
Regulatory reference	S.L.424.24 - Chemical Agents at Work Regulations (L.N.356 of 2021)
United Kingdom - Occupational Exposure Limits	
Local name	Methyl methacrylate
WEL TWA (mg/m ³)	208 mg/m ³
WEL TWA (ppm)	50 ppm

EuroI HPG 80W-140 TDL GL4/5

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)	
WEL STEL (mg/m ³)	416 mg/m ³
WEL STEL (OEL STEL) [ppm]	100 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Highly refined base oil (64741-88-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOELV TWA (mg/m ³)	5 mg/m ³
IOELV STEL (mg/m ³)	10 mg/m ³

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

Exposure-value for oil mist : 10 mg/m³ (15 min.) or 5 mg/m³ (8 hours).

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. In case of splash hazard: safety glasses. Eye protection should only be necessary where liquid could be splashed or sprayed.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Other skin protection

Materials for protective clothing:

PVC gloves. Neoprene or nitrile rubber gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment.

8.2.2.4. Thermal hazards

No additional information available

EuroI HPG 80W-140 TDL GL4/5

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Consumer exposure controls:

PVC gloves. Neoprene or nitrile rubber gloves.

Other information:

Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: brown.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: < -12 °C ASTM D 97
Freezing point	: Not available
Boiling point	: > 280 °C
Flammability (solid, gas)	: Non flammable.
Lower explosive limit (LEL)	: 0,6 vol %
Upper explosive limit (UEL)	: 7 vol %
Flash point	: 163 °C ASTM D 93
Auto-ignition temperature	: > 240 °C
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 200 – 300 mm ² /s at 40 °C, ASTM D 445
Solubility	: insoluble in water.
Log Kow	: Not available
Log Pow	: > 3
Vapour Pressure 20°C	: < 0,1 hPa
Vapour pressure at 50°C	: Not available
Density	: 0,89 – 0,91 kg/l ASTM D 4052
Relative density	: Not available
Relative vapour density at 20°C	: > 1 (air=1)
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Explosion limits : 0,6 – 7 vol %

9.2.2. Other safety characteristics

Relative evaporation rate (butylacetate=1) : < 0,1
VOC content : 0 %
Other properties : Gas/vapour heavier than air at 20°C

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

Euroil HPG 80W-140 TDL GL4/5

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.4. Conditions to avoid

Moisture. Overheating.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	> 5,53 mg/l

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 ml/kg
LC50 Inhalation - Rat (Vapours)	29,8 mg/l/4h

Magnesium metaborate (13703-82-7)

LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))

Polysulfides, di-tert-Bu (68937-96-2)

LD50 oral rat	> 2000 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg bodyweight

Highly refined base oil (64741-88-4)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat	> 5000 mg/m ³

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified

EuroI HPG 80W-140 TDL GL4/5

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)

STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)

NOAEL (oral, rat, 90 days)	2000 mg/kg bodyweight/day
NOAEC (inhalation, rat, vapour, 90 days)	25 mg/l

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl

NOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat
----------------------------	----------------------------------

Magnesium metaborate (13703-82-7)

NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
----------------------------	---

Polysulfides, di-tert-Bu (68937-96-2)

LOAEL (oral, rat, 90 days)	300 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.7 (Repeated Dose (28 Days) Toxicity (Oral))
NOAEL (oral, rat, 90 days)	100 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents), Guideline: EU Method B.7 (Repeated Dose (28 Days) Toxicity (Oral))

Aspiration hazard	: Not classified
-------------------	------------------

EuroI HPG 80W-140 TDL GL4/5

Viscosity, kinematic	200 – 300 mm ² /s at 40 °C, ASTM D 445
----------------------	---

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)

Viscosity, kinematic	1400 mm ² /s ASTM D 445
----------------------	------------------------------------

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14- tert-alkyl

Viscosity, kinematic	1692 mm ² /s
----------------------	-------------------------

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Other information : Toxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the toxicology of similar products, Likely route of exposure: ingestion, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Ecology - water	: This product floats on water and may affect the oxygen-balance in the water.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

EuroI HPG 80W-140 TDL GL4/5

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

LC50 fish 1	100 mg/l
EC50 Daphnia 1	10000 mg/l
EC50 72h - Algae [1]	> 100 mg/l

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)

LC50 fish 1	> 79 mg/l Oncorhynchus mykiss (Rainbow trout)
EC50 Daphnia 1	69 mg/l Daphnia magna (Water flea)
NOEC (chronic)	110 mg/l Selenastrum capricornutum
NOEC chronic fish	9,4 mg/l (OECD 210 method)
NOEC chronic crustacea	37 mg/l Daphnia magna (Water flea)

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl

LC50 fish 1	24 mg/kg Oncorhynchus mykiss (Rainbow trout)
LC50 fish 2	8,5 mg/kg Pimephales promelas
EC50 Daphnia 1	91,4 mg/l daphnia
EC50 72h - Algae [1]	6,4 mg/l selenastrum capricornutum
EC50 96h - Algae [1]	6,4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	15 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC chronic fish	3,2 mg/l Oncorhynchus mykiss (Rainbow trout)
NOEC chronic crustacea	0,12 mg/l daphnia
NOEC chronic algae	1,7 mg/l selenastrum capricornutum

Mineral Oil

LC50 fish 1	> 100 mg/l Pimephales promelas
EC50 Daphnia 1	> 10000 mg/l
EC50 72h - Algae [1]	> 100 mg/l Scenedesmus quadricauda

Polysulfides, di-tert-Bu (68937-96-2)

EC50 Daphnia 1	0,24 mg/l Daphnia magna (Water flea)
EC50 72h - Algae [1]	0,838 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

Highly refined base oil (64741-88-4)

LC50 fish 1	> 100 mg/l Pimephales promelas
EC50 Daphnia 1	> 10000 mg/l EC50 48h - Daphnia magna [mg/l]
EC50 72h - Algae [1]	> 100 mg/l Pseudokirchneriella subcapitata

EuroI HPG 80W-140 TDL GL4/5

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.2. Persistence and degradability

EuroI HPG 80W-140 TDL GL4/5

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)

Persistence and degradability	Readily biodegradable in water.
-------------------------------	---------------------------------

Biodegradation	94 % (OECD 301C method)
----------------	-------------------------

Mineral Oil

Biodegradation	31 % OECD TG 301 B
----------------	--------------------

12.3. Bioaccumulative potential

EuroI HPG 80W-140 TDL GL4/5

Log Pow	> 3
---------	-----

Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.
---------------------------	---

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)

Log Kow	1,38
---------	------

12.4. Mobility in soil

EuroI HPG 80W-140 TDL GL4/5

Ecology - soil	Not miscible with water. Spillages may penetrate the soil causing ground water contamination. This product floats on water and may affect the oxygen-balance in the water.
----------------	--

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Do not discharge into drains or the environment.
Additional information	: Hazardous waste.
Ecology - waste materials	: Every mixture with foreign substances such as solvents, brake- and cooling liquids is forbidden. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. When not empty dispose of this container at hazardous or special waste collection point.
European List of Waste (LoW, EC 2150/2002)	: 13 02 05* - mineral-based non-chlorinated engine, gear and lubricating oils

EuroI HPG 80W-140 TDL GL4/5

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated for transport				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

No data available

Transport by sea

No data available

Air transport

No data available

Inland waterway transport

No data available

Rail transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)	
Reference code	Applicable on
3(a)	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate

Euroil HPG 80W-140 TDL GL4/5

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EU restriction list (REACH Annex XVII)	
Reference code	Applicable on
3(b)	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] ; methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate ; Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14-tert-alkyl ; Mineral Oil ; Magnesium metaborate ; Polysulfides, di-tert-Bu
3(c)	Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl ; Polysulfides, di-tert-Bu
40.	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : 0 %

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

A chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Supersedes	Modified	
	Revision date	Modified	
	Flammability (solid, gas)	Added	
2.1	Adverse physicochemical, human health and environmental effects	Added	
4.1	First-aid measures after skin contact	Modified	
4.1	First-aid measures after inhalation	Modified	

EuroI HPG 80W-140 TDL GL4/5

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes			
Section	Changed item	Change	Comments
4.1	First-aid measures after ingestion	Modified	
4.1	First-aid measures after eye contact	Modified	
5.1	Suitable extinguishing media	Modified	
5.2	Hazardous decomposition products in case of fire	Added	
5.3	Protection during firefighting	Modified	
6.1	Protective equipment	Modified	
6.1	Emergency procedures	Modified	
6.2	Environmental precautions	Modified	
6.3	Methods for cleaning up	Modified	
6.3	Other information	Modified	
7.1	Precautions for safe handling	Modified	
7.1	Hygiene measures	Modified	
7.2	Storage conditions	Modified	
8.2	Environmental exposure controls	Modified	
8.2	Respiratory protection	Modified	
8.2	Hand protection	Modified	
8.2	Eye protection	Modified	
8.2	Appropriate engineering controls	Modified	
8.2	Skin and body protection	Modified	
9.1	Upper explosive limit (UEL)	Added	
9.1	Lower explosive limit (LEL)	Added	
9.1	Flash point	Modified	
9.1	Density	Modified	
9.1	Viscosity, kinematic	Modified	
9.1	Melting point	Modified	
10.6	Hazardous decomposition products	Added	
12.1	Ecology - general	Modified	
13.1	Product/Packaging disposal recommendations	Added	
15.2	Chemical safety assessment	Added	
16	Abbreviations and acronyms	Added	
16	Data sources	Added	
16	Other information	Added	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate

EuroI HPG 80W-140 TDL GL4/5

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:

BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
---------------------	-----------------------------------

EuroI HPG 80W-140 TDL GL4/5

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains Methyl methacrylate, Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentoxide, and salted by amines, C12-14- tert-alkyl, Magnesium metaborate. May produce an allergic reaction.
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.