



Eurol Coolant -36°C GLX-AV

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 14-4-2021 Revision date: 7-5-2026 Supersedes: 27-1-2025 Version: 3.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Eurol Coolant -36°C GLX-AV
UFI : P5WP-16Q6-6700-5PHU
Product code : E504030
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Intended for general public
Main use category : Industrial use, Professional use, Consumer use
Function or use category : Anti-freezing agents

1.3. Details of the supplier of the safety data sheet

Eurol B.V.
Energiestraat 12
NL-7442 DA Nijverdal
The Netherlands
Tel: +31 548 615 165
reach@eurol.com – www.eurol.com

1.4. Emergency telephone number

Emergency number : For Transport Emergency Call +31 88 303 7598 (24hr/day 7days/week)

Country/Area	Organisation	Emergency number
Ireland	National Poisons Information Centre. Beaumont Hospital. PO Box 1297. Beaumont Road 9 Dublin.	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)
Malta	Medicines & Poisons Info Office. Mater Dei Hospital. Msida MSD 2090 Msida.	112 +356 2545 6508
United Kingdom	National Poisons Information Service (Birmingham Centre). City Hospital. Dudley Road B18 7QH.	0344 892 0111 Only for healthcare professionals
	NHS 111/NHS 24/NHS Direct.	111 0845 4647 or call a doctor

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4 H302
Specific target organ toxicity – Repeated exposure, Category 2 H373
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

Eurol Coolant -36°C GLX-AV

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

GHS08

CLP Signal word :

Warning

Contains :

ethane-1,2-diol

Hazard statements (CLP) :

H302 - Harmful if swallowed.
H373 - May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).

Precautionary statements (CLP) :

P102 - Keep out of reach of children.
P260 - Do not breathe mist, vapours.
P270 - Do not eat, drink or smoke when using this product.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Child-resistant fastening :

Not applicable

Tactile warning :

Applicable

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	methyl-1H-benzotriazole (29385-43-1)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	methyl-1H-benzotriazole (29385-43-1)

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
ethane-1,2-diol substance with national workplace exposure limit(s) (IE, MT, GB); substance with a Community workplace exposure limit	CAS-No.: 107-21-1 EC-No.: 203-473-3 EC Index-No.: 603-027-00-1 REACH-no: 01-2119456816-28	≥ 50	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) STOT RE 2, H373
methyl-1H-benzotriazole	CAS-No.: 29385-43-1 EC-No.: 249-596-6 REACH-no: 01-2119979081-35	0,1 – 1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Repr. 2, H361d Aquatic Chronic 2, H411

Full text of H- and EUH-statements: see section 16

EuroL Coolant -36°C GLX-AV

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Rinse mouth. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: At normal ambient temperatures this product will be unlikely to present an inhalation hazard because of its low volatility. May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.
Symptoms/effects after skin contact	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after eye contact	: Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.
Symptoms/effects after ingestion	: Harmful if swallowed.
Symptoms/effects upon intravenous administration	: Unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Combustion generates: CO, CO ₂ .
Explosion hazard	: Not expected to be a fire/explosion hazard under normal conditions of use.

5.3. Advice for firefighters

Precautionary measures fire	: Do not enter fire area without proper protective equipment, including respiratory protection.
Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Prevent fire fighting water from entering the environment. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	--

For non-emergency personnel

Protective equipment	: Use protective clothing.
Emergency procedures	: Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

Eurol Coolant -36°C GLX-AV

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.3. Methods and material for containment and cleaning up

- For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak without risks if possible.
- Methods for cleaning up : Take up liquid spill into absorbent material.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.
- Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep container tightly closed and in well ventilated place.
- Storage conditions : Keep cool. Protect from sunlight.
- Incompatible products : Reacts vigorously with strong oxidizers and acids.
- Maximum storage period : 5 year
- Storage temperature : ≤ 40 °C
- Information on mixed storage : Keep away from : Oxidizing materials. Strong acids.
- Storage area : Store at ambient temperature.
- Special rules on packaging : Keep container tightly closed and dry.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

ethane-1,2-diol (107-21-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ethylene glycol
IOELV TWA (mg/m ³)	52 mg/m ³
IOELV TWA (ppm)	20 ppm
IOELV STEL (mg/m ³)	104 mg/m ³
IOELV STEL (ppm)	40 ppm
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Ireland - Occupational Exposure Limits	
Local name	Ethane-1,2-diol [Ethylene glycol]

Euroil Coolant -36°C GLX-AV

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethane-1,2-diol (107-21-1)	
OEL (8 hours ref) (mg/m ³)	10 mg/m ³ particulate 52 mg/m ³ vapour
OEL (8 hours ref) (ppm)	20 ppm vapour
OEL (15 min ref) (mg/m ³)	104 mg/m ³ vapour
OEL (15 min ref) (ppm)	40 ppm vapour
Remark	IOELV (Indicative Occupational Exposure Limit Values), Skin (Substances which have the capacity to penetrate intact skin when they come in contact with it and be absorbed into the body. A substantial contribution to the total body burden via dermal exposure is possible)
Regulatory reference	Chemical Agents Code of Practice 2024
Malta - Occupational Exposure Limits	
Local name	Ethylene glycol
OEL TWA (mg/m ³)	52 mg/m ³
OEL TWA (ppm)	20 ppm
OEL STEL (mg/m ³)	104 mg/m ³
OEL STEL (ppm)	40 ppm
Remark	Skin # Ġilda
Regulatory reference	S.L. 424.24 - Chemical Agents at Work Regulations (L.N. 356 of 2021) # L.S. 424.24 - Regolamenti dwar Aġenti Kimiċi fuq il-Post tax-Xogħol (A.L. 356 tal-2021)
United Kingdom - Occupational Exposure Limits	
Local name	Ethane-1,2-diol
WEL TWA (mg/m ³)	10 mg/m ³ particulate 52 mg/m ³ vapour
WEL TWA (ppm)	20 ppm vapour
WEL STEL (mg/m ³)	104 mg/m ³ vapour
WEL STEL (OEL STEL) [ppm]	40 ppm vapour
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment:

Gloves. In case of splash hazard: safety glasses. Eye protection should only be necessary where liquid could be splashed or sprayed.

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Safety glasses

Eurol Coolant -36°C GLX-AV

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Hand protection					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0.4		EN ISO 374
Disposable gloves	Butyl rubber	6 (> 480 minutes)	0.7		EN ISO 374

Other skin protection

Materials for protective clothing:

Neoprene or nitrile rubber gloves. Butyl-rubber protective gloves

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment.

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Consumer exposure controls:

Neoprene or nitrile rubber gloves. Butylrubber protective gloves.

Other information:

Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Blue.
Appearance	: Liquid.
Odour	: odourless.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: -37 °C
Boiling point	: > 100 °C
Flammability (solid, gas)	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: 111 °C
Auto-ignition temperature	: > 390 °C
Decomposition temperature	: Not available
pH	: Not available
pH solution	: 7 – 10
Viscosity, kinematic	: Not available
Solubility	: Miscible with water.
Log Kow	: Not available
Log Pow	: < -0,1
Vapour Pressure 20°C	: < 2 hPa
Vapour pressure at 50°C	: Not available
Density	: 1,06 – 1,08 kg/l ASTM D 4052
Relative density	: Not available
Relative vapour density at 20°C	: > 1 (air = 1)
Particle characteristics	: Not applicable

EuroI Coolant -36°C GLX-AV

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

9.2. Other information

Other safety characteristics

Relative evaporation rate (butylacetate=1) : < 0,1
Other properties : Gas/vapour heavier than air at 20°C

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

Moisture. Overheating.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

EuroI Coolant -36°C GLX-AV	
ATE CLP (oral)	962,649 mg/kg bodyweight
ethane-1,2-diol (107-21-1)	
LD50 oral rat	7712 mg/kg bodyweight Animal: rat
LD50 dermal	> 3500 mg/kg mouse
LC50 Inhalation - Rat	> 2,5 mg/l (6h)
methyl-1H-benzotriazole (29385-43-1)	
LD50 oral rat	≈ 720 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 700 - 800
LD50 oral	720 mg/kg
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
ethane-1,2-diol (107-21-1)	
pH	6 – 7,5
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met)

Eurool Coolant -36°C GLX-AV

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ethane-1,2-diol (107-21-1)	
pH	6 – 7,5
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).

ethane-1,2-diol (107-21-1)	
STOT-repeated exposure	May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).

methyl-1H-benzotriazole (29385-43-1)	
NOAEL (oral, rat, 90 days)	≈ 150 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

11.2. Information on other hazards

Other information

Other information : Toxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the toxicology of similar products, Likely route of exposure: ingestion, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic) : Not classified (Based on available data, the classification criteria are not met)

ethane-1,2-diol (107-21-1)	
LC50 fish 1	> 72860 mg/l Test organisms (species): Pimephales promelas
EC50 Daphnia 1	> 100 mg/l Test organisms (species): Daphnia magna
NOEC (chronic)	≥ 1000 mg/l Test organisms (species): Americamysis bahia (previous name: Mysidopsis bahia) Duration: '23 d'
NOEC chronic fish	15380 mg/l Pimephales promelas
NOEC chronic crustacea	8590 mg/l daphnia

methyl-1H-benzotriazole (29385-43-1)	
LC50 fish 1	55 mg/l Test organisms (species): Cyprinodon variegatus
EC50 Daphnia 1	55 mg/l Arcartia tonsa
EC50 other aquatic organisms 1	15,8 mg/l Test organisms (species): other aquatic crustacea:
EC50 other aquatic organisms 2	8,58 mg/l Test organisms (species): other aquatic crustacea:
EC50 72h - Algae [1]	53 mg/l Test organisms (species): Skeletonema costatum
LOEC (chronic)	37,6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	18,4 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

EuroI Coolant -36°C GLX-AV

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.2. Persistence and degradability

EuroI Coolant -36°C GLX-AV

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

ethane-1,2-diol (107-21-1)

Persistence and degradability	Readily biodegradable in water, easily degradable in the soil.
-------------------------------	--

Biochemical oxygen demand (BOD)	0,47 g O ₂ /g substance
---------------------------------	------------------------------------

Chemical oxygen demand (COD)	1,24 g O ₂ /g substance
------------------------------	------------------------------------

ThOD	1,29 g O ₂ /g substance
------	------------------------------------

BOD (% of ThOD)	0,36
-----------------	------

methyl-1H-benzotriazole (29385-43-1)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

12.3. Bioaccumulative potential

EuroI Coolant -36°C GLX-AV

Log Pow	< -0,1
---------	--------

ethane-1,2-diol (107-21-1)

Log Pow	-1,36
---------	-------

Bioaccumulative potential	No bioaccumulation.
---------------------------	---------------------

methyl-1H-benzotriazole (29385-43-1)

Log Pow	1,08
---------	------

12.4. Mobility in soil

ethane-1,2-diol (107-21-1)

Surface tension	0,048 N/m (20 °C)
-----------------	-------------------

12.5. Results of PBT and vPvB assessment

Component

Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	methyl-1H-benzotriazole (29385-43-1)
--	--------------------------------------

Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	methyl-1H-benzotriazole (29385-43-1)
---	--------------------------------------

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste disposal recommendations	: Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers.

Eurol Coolant -36°C GLX-AV

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

- Ecology - waste materials : Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. When not empty dispose of this container at hazardous or special waste collection point.
- European List of Waste (LoW, EC 2000/532) : 16 01 14* - antifreeze fluids containing dangerous substances
15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN
14.1. UN number or ID number			
Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name			
Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available			

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Eurol Coolant -36°C GLX-AV

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	Eurol Coolant -36°C GLX-AV ; ethane-1,2-diol	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Not listed on the Ozone Depletion list (Regulation EU 2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Indication of changes		
Section	Changed item	Comments
1.1	UFI on SDS 1.1	Modified
1.1	Name	Added
2.2	Precautionary statements (CLP)	Modified
4.2	Symptoms/injuries after ingestion	Modified
9	Relative vapour density at 20°C	Modified
10.4	Conditions to avoid	Modified
10.6	Hazardous decomposition products	Modified

Eurol Coolant -36°C GLX-AV

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Repr. 2	Reproductive toxicity, Category 2
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
H302	Harmful if swallowed.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).
H411	Toxic to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Acute Tox. 4 (Oral)	H302	Calculation method
STOT RE 2	H373	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.