



# Eurol Chain Lube Spray Road & Racing 400ML

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Issue date: 07.12.2015 Revision date: 21.11.2023 Supersedes: 30.01.2023 Version: 6.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : Eurol Chain Lube Spray Road & Racing 400ML  
Product code : E701311  
Vaporizer : Aerosol  
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : Industrial use, professional use, Consumer use

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Eurol B.V.  
Energiesstraat 12  
NL-7442 DA Nijverdal  
The Netherlands  
Tel: +31 548 615 165  
[reach@eurol.com](mailto:reach@eurol.com) – [www.eurol.com](http://www.eurol.com)

#### 1.4. Emergency telephone number

Emergency number : For Transport Emergency Call +31 6 26 71 27 43 (24hr/day 7days/week)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital Msida MSD 2090 Msida	+356 2545 6508	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229  
Specific target organ toxicity – Single exposure, Category 3, H336  
Narcosis  
Specific target organ toxicity – Repeated exposure, Category 1 H372  
Hazardous to the aquatic environment – Chronic Hazard, H412  
Category 3

# Eurol Chain Lube Spray Road & Racing 400ML

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements: see section 16

### Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. Causes damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

## 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

GHS08

CLP Signal word

: Danger

Contains

: Naphtha (petroleum), hydrodesulfurized heavy; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, aromatics (< 2%)

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.  
H229 - Pressurised container: May burst if heated.  
H336 - May cause drowsiness or dizziness.  
H372 - Causes damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation).  
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P102 - Keep out of reach of children.  
P210 - Keep away from heat, hot surfaces, open flames, sparks. No smoking.  
P251 - Do not pierce or burn, even after use.  
P264 - Wash hands thoroughly after handling.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

EUH-statements

: EUH208 - Contains Long-chain alkyl amine. May produce an allergic reaction.

Child-resistant fastening

: Applicable

Tactile warning

: Applicable

## 2.3. Other hazards

Other hazards not contributing to the classification : This product floats on water and may affect the oxygen-balance in the water. Flammable or explosive vapour/air mixtures may be formed.

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

# Eurol Chain Lube Spray Road & Racing 400ML

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butane substance with national workplace exposure limit(s) (GB, IE)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691-32	25 – 35	Flam. Gas 1A, H220 Press. Gas
Naphtha (petroleum), hydrodesulfurized heavy substance with a Community workplace exposure limit	CAS-No.: 64742-82-1 EC-No.: 265-185-4 REACH-no: 01-2119490979-12	10 – 25	Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
propane substance with national workplace exposure limit(s) (IE)	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944-21	10 – 25	Flam. Gas 1A, H220 Press. Gas
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, aromatics (< 2%)	EC-No.: 919-857-5 REACH-no: 01-2119463258-33	3 – 5	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304
Sulfonic acids, petroleum, sodium salts	CAS-No.: 68608-26-4 EC-No.: 271-781-5 REACH-no: 01-2119527859-22	3 – 5	Eye Irrit. 2, H319
Long-chain alkyl amine	CAS-No.: 68955-53-3 EC-No.: 273-279-1 REACH-no: 01-2119456798-18	0,1 – 1	Acute Tox. 4 (Oral), H302 (ATE=612 mg/kg bodyweight) Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Acute Tox. 2 (Inhalation), H330 Skin Corr. 1B, H314 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410
Long-chain alkenyl amine	CAS-No.: 112-90-3 EC-No.: 204-015-5	0,1 – 1	Acute Tox. 4 (Oral), H302 (ATE=1689 mg/kg bodyweight) Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.

# EuroL Chain Lube Spray Road & Racing 400ML

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.  
Symptoms/effects after inhalation : Inhalation of the spray or mist may produce severe irritation of respiratory tract, characterized by coughing, choking or shortness of breath. Symptoms of overexposure to vapours include drowsiness, weakness, headache, dizziness, nausea, vomiting, dimming of vision.  
Symptoms/effects after skin contact : Unlikely to cause harm to the skin on brief or occasional contact but prolonged or repeated exposure may lead to dermatitis. Causes skin irritation. Red skin.  
Symptoms/effects after eye contact : Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.  
Symptoms/effects after ingestion : Bad taste. Unlikely to cause harm if accidentally swallowed in small doses, though larger quantities may cause nausea and diarrhoea.  
Symptoms/effects upon intravenous administration : Unknown.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.  
Explosion hazard : Pressurised container: May burst if heated.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Advice for firefighters

Precautionary measures fire : Do not enter fire area without proper protective equipment, including respiratory protection.  
Firefighting instructions : Use water spray or fog for cooling exposed containers.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.  
Other information : Prevent fire fighting water from entering the environment. Sweep up and remove to a suitable, clearly marked container for disposal in accordance with local regulations.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Spill area may be slippery. Prevent soil and water pollution. Prevent entry to sewers and public waters. Eliminate every possible source of ignition. Keep out of reach of children. Ensure adequate ventilation, especially in confined areas.

#### 6.1.1. For non-emergency personnel

Protective equipment : When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required. Use protective clothing.  
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe dust/fume/gas/mist/vapours/spray.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".  
Emergency procedures : No specific measures are necessary.

### 6.2. Environmental precautions

Avoid release to the environment.

# EuroL Chain Lube Spray Road & Racing 400ML

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 6.3. Methods and material for containment and cleaning up

- For containment : Large quantities: Contain large spillage with sand or earth. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal.
- Methods for cleaning up : Mechanically recover the product.
- Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area.
- Handling temperature : < 45 °C
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep container tightly closed and in well ventilated place.
- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
- Incompatible products : Reacts vigorously with strong oxidizers and acids.
- Maximum storage period : 3 year
- Storage temperature : ≤ 50 °C
- Information on mixed storage : Keep away from : Oxidizing materials. Strong acids.
- Storage area : Store at ambient temperature. Keep out of direct sunlight. Keep container in a well-ventilated place.
- Special rules on packaging : Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

### 7.3. Specific end use(s)

Aerosol can.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

butane (106-97-8)	
Ireland - Occupational Exposure Limits	
Local name	Butane
OEL (8 hours ref) (ppm)	1000 ppm
OEL (15 min ref) (ppm)	1000 ppm
Regulatory reference	Chemical Agents Code of Practice 2021
United Kingdom - Occupational Exposure Limits	
Local name	Butane

# Eurol Chain Lube Spray Road & Racing 400ML

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>butane (106-97-8)</b>	
WEL TWA (mg/m <sup>3</sup> )	1450 mg/m <sup>3</sup>
WEL TWA (ppm)	600 ppm
WEL STEL (mg/m <sup>3</sup> )	1810 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	750 ppm
Remark (WEL)	Carc (Capable of causing cancer and/or heritable genetic damage. See paragraphs 49–51), (only applies if Butane contains more than 0.1% of buta-1,3-diene)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

<b>Naphtha (petroleum), hydrodesulfurized heavy (64742-82-1)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	White spirit Type 1
IOELV TWA (mg/m <sup>3</sup> )	116 mg/m <sup>3</sup>
IOELV TWA (ppm)	20 ppm
IOELV STEL (mg/m <sup>3</sup> )	290 mg/m <sup>3</sup>
IOELV STEL (ppm)	50 ppm
Notes	Skin. (Year of adoption 2007)
Regulatory reference	SCOEL Recommendations

<b>propane (74-98-6)</b>	
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Propane
OEL (8 hours ref) (ppm)	1000 ppm
Remark	Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants)
Regulatory reference	Chemical Agents Code of Practice 2021

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Gloves. High gas/vapour concentration: gas mask with filter type A. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Protective goggles.

# Eurol Chain Lube Spray Road & Racing 400ML

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Protective gloves

##### Other skin protection

##### Materials for protective clothing:

PVC gloves. Neoprene or nitrile rubber gloves

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment.

#### 8.2.2.4. Thermal hazards

No additional information available

#### 8.2.3. Environmental exposure controls

##### Environmental exposure controls:

Avoid release to the environment.

##### Consumer exposure controls:

PVC gloves. Neoprene or nitrile rubber gloves.

##### Other information:

Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Brownish.
Appearance	: Oily. Liquid.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: -42 – 400 °C Aerosol
Flammability (solid, gas)	: Extremely flammable aerosol
Explosive properties	: Pressurised container: May burst if heated.
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: Does not apply
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: > 21 mm <sup>2</sup> /s
Solubility	: insoluble in water.

# Eurol Chain Lube Spray Road & Racing 400ML

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Log Kow	: Not available
Vapour Pressure 20°C	: 8530 hPa
Vapour pressure at 50°C	: Not available
Density	: 0,85 kg/l
Relative density	: Not available
Relative vapour density at 20°C	: > 1 (air=1)
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 77,6 %

#### 9.2.2. Other safety characteristics

Relative evaporation rate (butylacetate=1) : 0,2  
VOC content : 60,38 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

Strong oxidizing agents. Strong acids.

### 10.6. Hazardous decomposition products

CO, CO<sub>2</sub>.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

<b>butane (106-97-8)</b>	
LD50 oral rat	≥ 5000 mg/kg
LD50 dermal rabbit	≥ 5000 mg/kg
LC50 Inhalation - Rat (Vapours)	≥ 50 mg/l/4h
<b>Naphtha (petroleum), hydrodesulfurized heavy (64742-82-1)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	3400 mg/kg
LC50 Inhalation - Rat (Dust/Mist)	13,1 mg/l/4h



# Eurol Chain Lube Spray Road & Racing 400ML

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>propane (74-98-6)</b>	
LD50 oral rat	≥ 5000 mg/kg
LD50 dermal rabbit	≥ 5000 mg/kg
LC50 Inhalation - Rat (Vapours)	≥ 50 mg/l/4h
<b>Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, aromatics (&lt; 2%)</b>	
LD50 oral rat	≥ 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	≥ 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat (Dust/Mist)	≥ 50 mg/l/4h
<b>Sulfonic acids, petroleum, sodium salts (68608-26-4)</b>	
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 1,9 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
<b>Long-chain alkyl amine (68955-53-3)</b>	
LD50 oral rat	612 mg/kg
LD50 dermal rat	251 ml/kg
LC50 Inhalation - Rat (Vapours)	1,19 mg/l/4h
<b>Long-chain alkenyl amine (112-90-3)</b>	
LD50 oral rat	1689 mg/kg
Skin corrosion/irritation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Serious eye damage/irritation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Respiratory or skin sensitisation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-single exposure	: May cause drowsiness or dizziness.
Additional information	: Based on available data, the classification criteria are not met
<b>Naphtha (petroleum), hydrodesulfurized heavy (64742-82-1)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, aromatics (&lt; 2%)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
<b>Long-chain alkyl amine (68955-53-3)</b>	
STOT-single exposure	May cause respiratory irritation.
<b>Long-chain alkenyl amine (112-90-3)</b>	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Causes damage to organs (central nervous system) through prolonged or repeated exposure (Inhalation).

# EuroI Chain Lube Spray Road & Racing 400ML

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Additional information : Based on available data, the classification criteria are not met

<b>Naphtha (petroleum), hydrodesulfurized heavy (64742-82-1)</b>	
STOT-repeated exposure	Causes damage to organs (central nervous system) through prolonged or repeated exposure.

<b>Sulfonic acids, petroleum, sodium salts (68608-26-4)</b>	
NOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

<b>Long-chain alkenyl amine (112-90-3)</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Additional information : Based on available data, the classification criteria are not met

<b>EuroI Chain Lube Spray Road &amp; Racing 400ML</b>	
Vaporizer	Aerosol
Viscosity, kinematic	> 21 mm <sup>2</sup> /s

<b>Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, aromatics (&lt; 2%)</b>	
Viscosity, kinematic	1,33 mm <sup>2</sup> /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm <sup>2</sup> /s)'

### 11.2. Information on other hazards

#### 11.2.1. Endocrine disrupting properties

No additional information available

#### 11.2.2. Other information

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

Other information : Toxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the toxicology of similar products, Likely route of exposure: ingestion, skin and eye.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.  
Ecology - water : This product floats on water and may affect the oxygen-balance in the water.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

<b>Naphtha (petroleum), hydrodesulfurized heavy (64742-82-1)</b>	
LC50 fish 1	10 – 30 mg/l
EC50 Daphnia 1	10 – 22 mg/l
EC50 72h - Algae [1]	4,6 – 10 mg/l

<b>Sulfonic acids, petroleum, sodium salts (68608-26-4)</b>	
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

# EuroL Chain Lube Spray Road & Racing 400ML

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Long-chain alkyl amine (68955-53-3)	
LC50 fish 1	0,11 mg/l
EC50 Daphnia 1	0,011 mg/l
EC50 72h - Algae [1]	0,03 mg/l

Long-chain alkenyl amine (112-90-3)	
LC50 fish 1	0,11 mg/l fish
EC50 Daphnia 1	0,011 mg/l daphnia
EC50 72h - Algae [1]	0,03 mg/l
ErC50 (algae)	0,03 mg/l ErC50 (algae)

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

EuroL Chain Lube Spray Road & Racing 400ML	
Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.

butane (106-97-8)	
Log Pow	2,89

### 12.4. Mobility in soil

EuroL Chain Lube Spray Road & Racing 400ML	
Ecology - soil	Not miscible with water. Spillages may penetrate the soil causing ground water contamination. This product floats on water and may affect the oxygen-balance in the water.

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

Additional information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Do not discharge into drains or the environment.
Additional information	: Hazardous waste.
Ecology - waste materials	: Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly. When not empty dispose of this container at hazardous or special waste collection point.

# EuroL Chain Lube Spray Road & Racing 400ML






## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

European List of Waste (LoW, EC 2000/532) : 16 05 04\* - gases in pressure containers (including halons) containing dangerous substances

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
<b>14.2. UN proper shipping name</b>				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
<b>Transport document description</b>				
UN 1950 AEROSOLS (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)), 2.1, (D)	UN 1950 AEROSOLS (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)), 2.1	UN 1950 Aerosols, flammable (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)), 2.1	UN 1950 AEROSOLS (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)), 2.1	UN 1950 AEROSOLS (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)), 2.1
<b>14.3. Transport hazard class(es)</b>				
2.1	2.1	2.1	2.1	2.1
				
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (UN) : 5F  
Special provisions (ADR) : 190, 327, 344, 625  
Limited quantities (ADR 2011) : 1I  
Excepted quantities (ADR) : E0  
Packing instructions (ADR) : P207  
Special packing provisions (ADR) : PP87, RR6, L2  
Mixed packing provisions (ADR) : MP9  
Transport category (ADR) : 2  
Special provisions for carriage - Packages (ADR) : V14  
Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV12  
Special provisions for carriage - Operation (ADR) : S2  
Tunnel restriction code (ADR) : D

#### Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959  
Packing instructions (IMDG) : P207, LP200  
Special packing provisions (IMDG) : PP87, L2  
EmS-No. (Fire) : F-D

# Eurol Chain Lube Spray Road & Racing 400ML

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

### Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

### Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

### Rail transport

Classification code (RID)	: 5F
Special provisions (RID)	: 190, 327, 344, 625
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P207, LP200
Special packing provisions (RID)	: PP87, RR6, L2
Mixed packing provisions (RID)	: MP9
Transport category (RID)	: 2
Special provisions for carriage – Packages (RID)	: W14
Special provisions for carriage - Loading, unloading and handling (RID)	: CW9, CW12
Colis express (express parcels) (RID)	: CE2
Hazard identification number (RID)	: 23

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

# EuroL Chain Lube Spray Road & Racing 400ML

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

### VOC Directive (2004/42)

VOC content : 60,38 %

### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

No additional information available

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Supersedes	Modified	
	Revision date	Modified	
	Flammability (solid, gas)	Modified	
2.1	Adverse physicochemical, human health and environmental effects	Added	
3	Composition/information on ingredients	Modified	
4.1	First-aid measures after eye contact	Modified	
4.1	First-aid measures general	Modified	
4.1	First-aid measures after skin contact	Modified	
4.1	First-aid measures after inhalation	Modified	
4.1	First-aid measures after ingestion	Modified	
4.2	Symptoms/effects	Modified	
5.1	Suitable extinguishing media	Modified	
5.2	Hazardous decomposition products in case of fire	Added	
5.2	Fire hazard	Modified	
5.2	Explosion hazard	Modified	
5.3	Protection during firefighting	Modified	
6.1	Protective equipment	Modified	
6.1	Emergency procedures	Modified	
6.2	Environmental precautions	Modified	
6.3	Methods for cleaning up	Modified	
6.3	Other information	Modified	
7.1	Precautions for safe handling	Modified	
7.1	Hygiene measures	Modified	

# Euroil Chain Lube Spray Road & Racing 400ML

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes			
Section	Changed item	Change	Comments
7.2	Storage conditions	Modified	
8.2	Environmental exposure controls	Modified	
8.2	Respiratory protection	Modified	
8.2	Hand protection	Modified	
8.2	Appropriate engineering controls	Modified	
8.2	Skin and body protection	Modified	
9.1	Melting point	Added	
9.1	Explosive properties	Added	
9.1	Relative vapour density at 20°C	Modified	
10.1	Reactivity	Modified	
10.4	Conditions to avoid	Modified	
12.1	Ecology - general	Modified	
13.1	Product/Packaging disposal recommendations	Added	
16	Abbreviations and acronyms	Modified	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration

# Euroil Chain Lube Spray Road & Racing 400ML

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains Long-chain alkyl amine. May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 3	Flammable liquids, Category 3
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.



# Euro! Chain Lube Spray Road & Racing 400ML

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Press. Gas	Gases under pressure
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Aerosol 1	H222;H229	On basis of test data
STOT SE 3	H336	Calculation method
STOT RE 1	H372	Calculation method
Aquatic Chronic 3	H412	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.