

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 13.03.2014 Revision date: 29.11.2023 Supersedes: 19.12.2022 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : Eurol Diesel Clean Direct

Product code : E802495

Type of product : Organic solvent

Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public

Main use category : Industrial use, professional use, Consumer use

Use of the substance/mixture : Organic solvent

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Eurol B.V. Energiestraat 12 NL-7442 DA Nijverdal The Netherlands Tel: +31 548 615 165

reach@eurol.com - www.eurol.com

1.4. Emergency telephone number

Emergency number : For Transport Emergency Call +31 6 26 71 27 43 (24hr/day 7days/week)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital Msida MSD 2090 Msida	+356 2545 6508	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals
United Kingdom	NHS 111/NHS 24/NHS Direct		111 0845 4647	or call a doctor

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aspiration hazard, Category 1 H304

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

May be fatal if swallowed and enters airways.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS08

CLP Signal word : Danger

Contains : Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics; Hydrocarbons,

C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics; Distillates (petroleum),

hydrotreated heavy paraffinic

Hazard statements (CLP) : H304 - May be fatal if swallowed and enters airways.

Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P301+P310+P331 - IF SWALLOWED: Immediately call a POISON CENTER, a doctor. Do

NOT induce vomiting. P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation. EUH066 - Repeated exposure may cause skin dryness or cracking.

Child-resistant fastening : Applicable Tactile warning : Applicable

2.3. Other hazards

FUH-statements

Other hazards not contributing to the classification

This product floats on water and may affect the oxygen-balance in the water. Material can accumulate some static charge during transfer. Flammable or explosive vapour/air mixtures may be formed.

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	EC-No.: 926-141-6 REACH-no: 01-2119456620- 43	≥ 50	Asp. Tox. 1, H304
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS-No.: 64742-48-9 EC-No.: 918-481-9 REACH-no: 01-2119457273- 39	10 – 25	Asp. Tox. 1, H304
2-Ethylhexan-1-ol substance with national workplace exposure limit(s) (GB, IE, MT); substance with a Community workplace exposure limit	CAS-No.: 104-76-7 EC-No.: 203-234-3 REACH-no: 01-2119487289- 20	3 – 5	Acute Tox. 4 (Inhalation), H332 (ATE=1,5 mg/l/4h) Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.]	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627- 25	1 – 3	Asp. Tox. 1, H304

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : High concentration of vapours may induce: headache, dizziness, drowsiness, nausea and

vomiting.

Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : Unlikely to cause more than transient stinging or redness if accidental eye contact occurs.

Contact with the eyes is likely to be irritating. Harmful: may cause lung damage if

swallowed.

Symptoms/effects after ingestion : Risk of lung oedema.

Symptoms/effects upon intravenous administration : Unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustion generates: CO, CO2.

Explosion hazard : May form flammable/explosive vapour-air mixture.

Hazardous decomposition products in case of fire : CO, CO2.

5.3. Advice for firefighters

Precautionary measures fire : Do not enter fire area without proper protective equipment, including respiratory protection.

Firefighting instructions : Use water spray or fog for cooling exposed containers.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

Other information : Prevent fire fighting water from entering the environment. Sweep up and remove to a

suitable, clearly marked container for disposal in accordance with local regulations. Heavier than air, vapours may travel long distances along ground, ignite and flash back to source.

29.11.2023 (Revision date) EN (English) 3/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Prevent soil and water pollution. Spill area may be slippery. Prevent build-up of electrostatic

charges (e.g, by grounding). Remove all sources of ignition.

6.1.1. For non-emergency personnel

Protective equipment : When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of

splashing) then chemical resistant aprons and/or impervious chemical suits and boots will

be required.

Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

Emergency procedures : No specific measures are necessary.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain large spillage with sand or earth.

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : In use, may form flammable vapour-air mixture. Empty containers retain product residue

(solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum

reconditioner or disposed of properly.

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.

Hygiene measures : Do no eat, drink or smoke when using this product. Always wash hands after handling the

product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Store in a dry place. Store in a closed container. Store away from direct sunlight or other

heat sources.

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

Incompatible products : Reacts vigorously with strong oxidizers and acids.

Maximum storage period : 5 year Storage temperature : \leq 40 °C

Information on mixed storage : Keep away from : Oxidizing materials. Strong acids.

Storage area : Store at ambient temperature.

Special rules on packaging : Keep container tightly closed and dry.

7.3. Specific end use(s)

No additional information available

29.11.2023 (Revision date) EN (English) 4/14

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

2-Ethylhexan-1-ol (104-76-7)			
EU - Indicative Occupational Exposure Limit (IOEL)			
Local name	2-ethylhexan-1-ol		
IOELV TWA (mg/m³)	5,4 mg/m³		
IOELV TWA (ppm)	1 ppm		
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164		
Ireland - Occupational Exposure Limits	Ireland - Occupational Exposure Limits		
Local name	2-Ethylhexan-1-ol		
OEL (8 hours ref) (mg/m³)	5,4 mg/m³		
OEL (8 hours ref) (ppm)	1 ppm		
Remark	IOELV (Indicative Occupational Exposure Limit Values)		
Regulatory reference	Chemical Agents Code of Practice 2021		
Malta - Occupational Exposure Limits			
Local name	2-Ethylhexan-1-ol		
OEL TWA (mg/m³)	5,4 mg/m³		
OEL TWA (ppm)	1 ppm		
Regulatory reference	S.L.424.24 - Chemical Agents at Work Regulations (L.N.356 of 2021)		
United Kingdom - Occupational Exposure Limits			
Local name	2-ethylhexan-1-ol		
WEL TWA (mg/m³)	5,4 mg/m³		
WEL TWA (ppm)	1 ppm		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. In case of splash hazard: safety glasses. Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Personal protective equipment symbol(s):







8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Other skin protection

Materials for protective clothing:

Neoprene or nitrile rubber gloves. Chemical resistant gloves (according to European standard NF ISO 374-1 or equivalent)

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Consumer exposure controls:

Provide good ventilation in process area to prevent formation of vapour. Neoprene or nitrile rubber gloves.

Other information:

Do not put the product-soaked rags into the pockets of working clothes. Do not use cloths stained with the product to dry hands. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : brown. Appearance : Liquid. Odour : characteristic. Odour threshold : Not available Melting point : Not applicable Freezing point : Not available : > 100 °C Boiling point Flammability (solid, gas) : Non flammable. Lower explosive limit (LEL) : 0,6 vol % Upper explosive limit (UEL) : 7 vol %

Flash point : > 62 °C ASTM D 93

Auto-ignition temperature : > 200 °C

Decomposition temperature : Not available
pH : Not available

Viscosity, kinematic : $2-4.5 \text{ mm}^2\text{/s}$ at 40 °C, ASTM D 445

Solubility : insoluble in water. Log Kow : Not available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Log Pow : > 3
Vapour Pressure 20°C : < 3 hPa
Vapour pressure at 50°C : Not available

Density : 0,815 – 0,825 kg/l ASTM D 4052

Relative density : Not available
Relative vapour density at 20°C : > 1 (air = 1)
Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Explosion limits : 0,6 – 7 vol %

9.2.2. Other safety characteristics

Relative evaporation rate (butylacetate=1) : < 0,1

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid

Keep away from naked flames/heat.

10.5. Incompatible materials

Strong oxidizing agents. strong acids.

10.6. Hazardous decomposition products

CO, CO2.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	
LD50 oral rat > 5000 mg/kg	
LD50 dermal rabbit	> 5000 mg/l (OECD 402 method)
LC50 Inhalation - Rat 5000 mg/m³	

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)	
LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	≥ 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)		
LC50 Inhalation - Rat	> 4,9 mg/l (OECD 403 method)	
2-Ethylhexan-1-ol (104-76-7)		
LD50 oral rat	≈ 2047 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LD50 dermal rabbit	> 3000 mg/kg	
LC50 Inhalation - Rat	0,89 – 5,3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:	
LC50 Inhalation - Rat [ppm]	> 227 ppm 6h	
LC50 Inhalation - Rat (Dust/Mist)	5,3 mg/l/4h	
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)		
LD50 oral rat	> 5000 mg/kg	
LD50 dermal rat	> 2000 mg/kg	
LC50 Inhalation - Rat	> 5,53 mg/l	
Skin corrosion/irritation : Serious eye damage/irritation : Respiratory or skin sensitisation : Germ cell mutagenicity : Carcinogenicity : Reproductive toxicity : STOT-single exposure :	Not classified	
2-Ethylhexan-1-ol (104-76-7)		
STOT-single exposure	May cause respiratory irritation.	
STOT-repeated exposure :	Not classified	
2-Ethylhexan-1-ol (104-76-7)		
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
NOAEC (inhalation, rat, gas, 90 days)	120 ppm Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)	
Aspiration hazard :	May be fatal if swallowed and enters airways.	
Eurol Diesel Clean Direct		
Viscosity, kinematic	2 – 4,5 mm ² /s at 40 °C, ASTM D 445	
Hydrocarbons, C11-C14, n-alkanes, isoalkane	es, cyclics, <2% aromatics	
Viscosity, kinematic	1,7 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)		
Viscosity, kinematic	1,8 mm²/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm²/s)'	
11.2. Information on other hazards		

11.2. Information on other hazards

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse

effects in the environment.

Ecology - water This product floats on water and may affect the oxygen-balance in the water.

Hazardous to the aquatic environment, short-term

Hazardous to the aquatic environment, long-term

: Not classified

: Not classified

(chronic)

,		
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics		
LC50 fish 1	1000 mg/l (96h; Oncorhynchus mykiss)	
LC50 other aquatic organisms 1	1000 mg/l (72h; Pseudokirchneriella subcapitata)	
EC50 Daphnia 1	1000 mg/l (48h; Daphnia magna)	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)		
LC50 fish 1	> 1000 mg/l Oncorhynchus mykiss (Rainbow trout)	
EC50 Daphnia 1	> 1000 mg/l EC50 48h - Daphnia magna [mg/l]	
EC50 72h - Algae [1]	> 1000 mg/l Pseudokirchneriella subcapitata	
2-Ethylhexan-1-ol (104-76-7)		
LC50 fish 1	17,1 mg/l Test organisms (species): Leuciscus idus melanotus	
LC50 fish 2	28,2 mg/l Test organisms (species): Pimephales promelas	
EC50 Daphnia 1	39 mg/l Test organisms (species): Daphnia magna	
EC50 72h - Algae [1]	11,5 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)	
EC50 72h - Algae [2]	16,6 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)	
ErC50 (other aquatic plants)	16,6 mg/l	
NOEC (acute)	14 mg/l	

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

LC50 fish 1	100 mg/l
EC50 Daphnia 1	10000 mg/l
EC50 72h - Algae [1]	> 100 mg/l

12.2. Persistence and degradability

Eurol Diesel Clean Direct		
Persistence and degradability Major constituents are expected to be inherently biodegradable, but the product components that may persist in the environment.		
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)		
Biodegradation 80 %		
2-Ethylhexan-1-ol (104-76-7)		
Biodegradation 100 %		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.3. Bioaccumulative potential

Eurol Diesel Clean Direct		
Log Pow	> 3	
Bioaccumulative potential	This product is not expected to bioaccumulate through food chains in the environment.	
2-Ethylhexan-1-ol (104-76-7)		
Bioconcentration factor (BCF REACH)	25,35 Calculation method	
Log Kow	2,9	

12.4. Mobility in soil

Eurol Diesel Clean Direct	
Ecology - soil Not miscible with water. Spillages may penetrate the soil causing ground water contamination.	
2-Ethylhexan-1-ol (104-76-7)	
Mobility in soil	-1,42

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation

Product/Packaging disposal recommendations

Waste disposal recommendations

: Disposal must be done according to official regulations.

 $: \ \, \text{Dispose of contents/container in accordance with licensed collector's sorting instructions}.$

: Dispose in a safe manner in accordance with local/national regulations. Do not discharge

into drains or the environment.

Additional information : Hazardous waste.

Ecology - waste materials : When not empty dispose of this container at hazardous or special waste collection point.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID	
14.1. UN number or ID n	14.1. UN number or ID number				
Not regulated for transport					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.2. UN proper shipping name					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
14.3. Transport hazard class(es)					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No Environment:		Dangerous for the environment: No	Dangerous for the environment: No	
No supplementary information available				

14.6. Special precautions for user

Overland transport

No data available

Transport by sea

No data available

Air transport

No data available

Inland waterway transport

No data available

Rail transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	
3(b)	Eurol Diesel Clean Direct; Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics; Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics; 2-Ethylhexan-1-ol; Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.]	

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of change	95			
Section	Changed item	Change	Comments	
	Supersedes	Modified		
	Revision date	Modified		
	Flammability (solid, gas)	Added		
1.1	UFI on SDS 1.1	Added		
2.1	Adverse physicochemical, human health and environmental effects Added			
4.1	First-aid measures general	Modified		
4.1	First-aid measures after skin contact	Modified		
4.1	First-aid measures after inhalation	Modified		
4.1	First-aid measures after ingestion	First-aid measures after ingestion Modified		
4.1	First-aid measures after eye contact	measures after eye contact Modified		
4.2	Symptoms/injuries after skin contact	Modified		
4.2	Symptoms/injuries after ingestion	Modified		
5.1	Suitable extinguishing media	Suitable extinguishing media Modified		
5.3	Protection during firefighting	Modified		
6.1	Protective equipment	Modified		
6.1	Emergency procedures	Modified		
6.2	Environmental precautions	Modified		
6.3	Methods for cleaning up	Modified		
6.3	Other information Modified			
7.1	Precautions for safe handling	Modified		
7.1	Hygiene measures	Hygiene measures Modified		
7.2	Storage conditions	Storage conditions Modified		
8.2	Environmental exposure controls	sure controls Modified		
8.2	Respiratory protection	atory protection Modified		
8.2	Hand protection	Modified		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes			
Section	Changed item	Change	Comments
8.2	Eye protection	Modified	
8.2	Appropriate engineering controls	Modified	
8.2	Skin and body protection Modified		
9.1	Melting point	Added	
9.1	Upper explosive limit (UEL)	Added	
9.1	Lower explosive limit (LEL)	Added	
9.1	Flash point	Modified	
9.1	Density	Modified	
9.1	Viscosity, kinematic	Modified	
12.1	Ecology - general	Modified	
13.1	Product/Packaging disposal recommendations	Added	
15.2	Chemical safety assessment	Added	
16	Abbreviations and acronyms	Added	
16	Data sources	Added	
16	Other information	Added	

Abbreviations and acronyms:			
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways		
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road		
ATE	Acute Toxicity Estimate		
BCF	Bioconcentration factor		
BLV	Biological limit value		
BOD	Biochemical oxygen demand (BOD)		
COD	Chemical oxygen demand (COD)		
DMEL	Derived Minimal Effect level		
DNEL	Derived-No Effect Level		
EC-No.	European Community number		
EC50	Median effective concentration		
EN	European Standard		
IARC	International Agency for Research on Cancer		
IATA	International Air Transport Association		
IMDG	International Maritime Dangerous Goods		
LC50	Median lethal concentration		
LD50	Median lethal dose		
LOAEL	Lowest Observed Adverse Effect Level		
NOAEC	No-Observed Adverse Effect Concentration		
NOAEL	No-Observed Adverse Effect Level		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:			
NOEC	No-Observed Effect Concentration		
OECD	Organisation for Economic Co-operation and Development		
OEL	Occupational Exposure Limit		
PBT	Persistent Bioaccumulative Toxic		
PNEC	Predicted No-Effect Concentration		
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail		
SDS	Safety Data Sheet		
STP	Sewage treatment plant		
ThOD	Theoretical oxygen demand (ThOD)		
TLM	Median Tolerance Limit		
VOC	Volatile Organic Compounds		
CAS-No.	Chemical Abstract Service number		
N.O.S.	Not Otherwise Specified		
vPvB	Very Persistent and Very Bioaccumulative		
ED	Endocrine disrupting properties		

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and

amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements:			
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4		
Asp. Tox. 1	Aspiration hazard, Category 1		
EUH066	Repeated exposure may cause skin dryness or cracking.		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
H304	May be fatal if swallowed and enters airways.		
H315	Causes skin irritation.		
H319	Causes serious eye irritation.		
H332	Harmful if inhaled.		
H335	May cause respiratory irritation.		
Skin Irrit. 2	Skin corrosion/irritation, Category 2		
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation		

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP		
Asp. Tox. 1	H304	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.