



Quality is in our nature

Passenger car engine oils - mid SAPS

# Motion 5W-40 C3

## Beschreibung

### Specifications

#### Performance level

API SN/CF

ACEA C3

VW 502.00

VW 505.01

MB 229.31

MB 226.5

BMW Longlife-04

Porsche A40

Renault RN0710

Renault RN0700

GM dexos 2

Ford WSS-M2C917-A

#### Recommended for use

Fiat 9.55535-T2

Fiat 9.55535-S2

Fiat 9.55535-GH2

### Physikalische Eigenschaften

| Farbe                             | Bernsteinfarben |             |
|-----------------------------------|-----------------|-------------|
| Dichte bei 20°C                   | 0.852 kg/L      | ASTM D 1298 |
| Viskosität, kinematisch bei 40°C  | 86.5 cSt        | ASTM D 445  |
| Viskosität, kinematisch bei 100°C | 14.3 cSt        | ASTM D 445  |
| Viscosity Index                   | 172             | ASTM D 2270 |
| Viskosität, dynamisch (CCS)       | 6140 cP         | ASTM D 2602 |
| Base number                       | 7.5 mg KOH/g    | ASTM D 2896 |
| Sulphated ash                     | 0.79 wt%        | ASTM D 874  |
| Flammpunkt                        | 197 °C          | ASTM D 93   |
| Pour point                        | -42 °C          | ASTM D 97   |

M01053

Version 1.0, 25-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com