



Quality is in our nature

Passenger car engine oils - mid SAPS

Motion 5W-40 C3

Description

Specifications

<u>Performance level</u>	GM dexos 2
API SN/CF	Ford WSS-M2C917-A
ACEA C3	<u>Recommended for use</u>
VW 502.00	Fiat 9.55535-T2
VW 505.01	Fiat 9.55535-S2
MB 229.31	Fiat 9.55535-GH2
MB 226.5	
BMW Longlife-04	
Porsche A40	
Renault RN0710	
Renault RN0700	

Physical properties

Colour	Amber	
Density at 20°C	0.852 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	86.5 cSt	ASTM D 445
Viscosity, kinematic at 100°C	14.3 cSt	ASTM D 445
Viscosity Index	172	ASTM D 2270
Viscosity, dynamic (CCS)	6140 cP	ASTM D 2602
Base number	7.5 mg KOH/g	ASTM D 2896
Sulphated ash	0.79 wt%	ASTM D 874
Flash point	197 °C	ASTM D 93
Pour point	-42 °C	ASTM D 97

M01053

Version 1.0, 25-03-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com