



Eurol Grease EG-0/101

Lubrication grease for use at exceptionally high loads

Beschreibung

Eurol Grease EG-0/101 with Eurol SYNGIS Technology is a (NLGI 0) lubricating grease developed for extreme applications combined with exceptional high loads. Especially useful in e.g. the paper, cement and steel industry or for heavy equipment in offshore and shipping.

Eurol Grease EG-0/101 is suitable for lubrication of:

- Open bearings
- Open gears
- Gear / worm transmissions

Gebrauchsanweisung

Remove old grease residue from the system or lubrication point as much as possible and clean thoroughly. Suitable for automatic lubrication systems.

Eurol Grease EG-0/101 hat folgende Eigenschaften

Very resistant against water wash out and spray off
Extreme protection against corrosion
Resistant to shock loads
Oxidation- and thermal stable
Superior mechanical stability
Almost no oil bleeding so very suitable for automatic lubrication systems
Economical in use

Physikalische Eigenschaften

Farbe	Dunkelbraun		
NLGI Konsistenzklasse	0		ASTM D 217
Verdickertyp	Calcium Complex		
Dichte bei 20°C	1.01	kg/L	ASTM D 1298
Grundöl Viskosität	700	cSt	ASTM D 445
Base oil type	Mineral		
Temperaturbereich	-25 – 150	°C	
4-ball weld load	750	kg	

Greases - Artikelnummer S005130
Version 1.0, 11-02-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Niederlande, tel. +31 548 61 51 65, www.eurolspecialty.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.