



Eurol Specialty Racing 75W-140

High performance transmission oil for racing applications

Beschreibung

Eurol Specialty Racing 75W-140 is a fully synthetic racing transmission oil based on Eurol SYNGIS Technology. This additive technology ensures high power output and unmatched protection against wear in the most extreme conditions.

Developed for competition use. It has been approved for use in gearboxes and differentials, with or without limited-slip capability. Recommended for use in sequential gearboxes with dog clutches.

Eurol Specialty Racing 75W-140 has won awards in:

- WTCR with Comtoyou Racing
- Dakar Rally with Toyota GAZOO Racing and Overdrive Racing

Gebrauchsanweisung

Flush the transmission or differential using Eurol Additive-S Flush in the old gear oil.

Drain the old oil and change the filter if present.

Note: Eurol Specialty Racing 75W-140 is not recommended for street use. In case of any application-related questions, please visit www.eurol.com/racing

Eurol Specialty Racing 75W-140 hat folgende Eigenschaften

Extreme wear protection, exceptional protection against pitting

Up to 80% wear reduction, compared with other racing gear oils

Outstanding detergency, excellent gearbox cleanliness

Virtually no viscosity loss during use, extending gearbox life

Outstanding protection of dog clutches, ensuring transmission stays in gear

Physikalische Eigenschaften

Farbe	Rot		
Dichte bei 20°C	0.884	kg/L	ASTM D 1298
Viskosität, kinematisch bei 40°C	246.4	cSt	ASTM D 445
Viskosität, kinematisch bei 100°C	31.1	cSt	ASTM D 445
Viskositätsindex	168		ASTM D 2270
Flammpunkt	180	°C	ASTM D 93
Stockpunkt	-42	°C	ASTM D 97