



## Eurol Chain Lube S-AC 38 FD Spray 400ML

Food grade chain / rope lubricant

### Description

Eurol Chain Lube S-AC 38 FD with SYNGIS Technology is developed for the lubrication of chains, ropes and joints. This professional lubricant is suitable for applications where excellent lubrication, creeping and penetration properties are required.

Eurol Chain Lube S-AC 38 FD Spray is food grade InS H1 / NSF H1 certified, making it suitable for incidental food contact in, among others, the food industry, pharmaceutical industry, food service and agriculture.

### Instructions for use

Clean and degrease parts thoroughly  
Shake well before use  
Apply a thin film  
Allow the product to penetrate  
Remove excess product with a clean cloth  
Do not spray on a hot surface  
Eurol Chain Lube S-AC 38 FD can be used in a temperature range from -20°C to +80°C

### Eurol Chain Lube S-AC 38 FD Spray 400ML has the following characteristics

InS H1, 1797231

Excellent anti wear properties  
Excellent protection against corrosion  
Very good water repellent properties  
Very good creeping and penetration properties  
Loosens corroded and stuck parts  
Low friction coefficient  
Reduces energy consumption  
Economical in use

### Physical properties

|                               |        |      |             |
|-------------------------------|--------|------|-------------|
| Colour                        | Yellow |      |             |
| Density at 20°C               | 0.937  | kg/l | ASTM D 1298 |
| Viscosity, kinematic at 40°C  | 32     | cSt  | ASTM D 445  |
| Viscosity, kinematic at 100°C | 6.5    | cSt  | ASTM D 445  |
| Viscosity Index               | 162    |      | ASTM D 2270 |

Industrial oils - Chain - Article number S001101AER  
Version 1.1, 18-06-2020

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, [www.eurolspecialty.com](http://www.eurolspecialty.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.