

specialty lubricants

Eurol Chain Lube S-AC 38 FD Spray 400ML

Food grade chain / rope lubricant

Article number S001101AER Version 1.2 20/03/2025

Produktinformationen

Eurol Chain Lube S-AC 38 FD Spray with SYNGIS Technology is developed for the lubrication of chains, cables, and joints. This professional lubricant is extremely suitable for applications where excellent lubrication properties (creeping and penetration properties) are required.

Eurol Chain Lube S-AC 38 FD Spray is food-grade InS H1 / NSF H1 certified and thus suitable for incidental food contact for, among others, the food industry, pharmaceutical industry, hospitality, agriculture, and arable farming.

Product benefits

- NSF H1, 162325
- Excellent anti-wear properties
- Excellent corrosion protection
- Very good water-repellent properties
- Very good creeping and penetration properties
- · Loosens rusted and stuck parts
- · Low friction coefficient
- · Reduces energy consumption
- · Economical in use

Instructions for use

- · Clean and degrease parts thoroughly.
- · Shake well before use.
- · Apply a thin film.
- Allow the product to take effect.
- · Remove excess product.
- Do not spray on a hot surface.
- Eurol Chain Lube S-AC 38 FD can be used within a temperature range of -20°C to +80°C.

Physical properties

Characteristic	Value/Result	ASTM Standard
Color	Yellow	
Density at 20°C	0.94 kg/l	ASTM D 4052
Viscosity, kinematic at 40 °C	32.0 cSt	ASTM D 445
Viscosity, kinematic at 100 °C	6.5 cSt	ASTM D 445
Viscosity index	162	ASTM D 2270