

specialty lubricants

Eurol Chain Lube S-AC 38 FD

Food grade chain / rope lubricant

Description

Eurol Chain Lube S-AC 38 FD with SYNGIS Technology is developed for the lubrication of chains, ropes and joints. This professional lubricant is suitable for applications where excellent lubrication, creeping and penetration properties are required. Eurol Chain Lube S-AC 38 FD is especially suitable for sewing machines.

Eurol Chain Lube S-AC 38 FD is food grade NSF H1 certified, making it suitable for incidental food contact in, among others, the food industry, pharmaceutical industry, food service and agriculture.

Instructions for use

Clean and degrease parts thoroughly Shake well before use Apply a thin film by brush Allow the product to penetrate Remove excess product with a clean cloth Eurol Chain Lube S-AC 38 FD can be used in a temperature range from -20°C to +80°C

Eurol Chain Lube S-AC 38 FD has the following characteristics

NSF H1, 161461 Excellent anti wear properties Excellent protection against corrosion Very good water repellent properties Very good creeping and penetration properties Loosens corroded and stuck parts Low friction coefficient Reduces energy consumption Economical in use

Physical properties

Yellow		
0.937	kg/l	ASTM D 1298
32	cSt	ASTM D 445
6.5	cSt	ASTM D 445
162		ASTM D 2270
62	°C	ASTM D 93
0	°C	ASTM D 97
	0.937 32 6.5 162	0.937 kg/l 32 cSt 6.5 cSt 162 62 °C

Industrial oils - Chain - Article number S001101 Version 1.2, 11-10-2023

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturers instructions.