

# specialty lubricants



# **Eurol Food Gear HV 220**

# Food grade synthetic gearbox oil

Article number \$002107 Version 1.1 16/04/2025

#### **Product information**

Eurol Food Gear HV 220 (ISO 220) with SYNGIS Technology is a professional, synthetic gearbox oil, applicable for gearbox lubrication, general machinery lubrication, transport chains, drive chains, rotary vane blowers, and circulation lubrication.

Eurol Food Gear HV 220 is food-grade InS H1 / NSF H1 certified and thus suitable for incidental food contact for, among others, the food industry, pharmaceutical industry, hospitality, agriculture, and arable farming.

#### **Product benefits**

- NSF H1, 161490
- Excellent anti-wear/extreme pressure properties
- Excellent water separation
- Excellent corrosion protection
- · High viscosity index and stable against shear forces
- Oxidation and thermally stable
- Low friction coefficient, leading to reduced energy consumption
- · Long service intervals
- · Economical in use
- DIN 51524/3
- DIN 51517/3
- DIN 51506
- HLP HC, CLP, HC, VDL

#### Application

· Automatic lubrication systems

## **Usage instructions**

· Remove the old oil from the system and flush thoroughly.

#### **Performance level**

- DIN 51506: VDL
- DIN 51517/3 (CLP)
- DIN 51524/3 (HVLP)

### Physical properties

Characteristic	Value/Result	ASTM Standard
Color	Colourless	
Density at 20°C	0.85 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	220.0 cSt	ASTM D 445
Viscosity, kinematic at 100°C	28.9 cSt	ASTM D 445
Viscosity Index	170	ASTM D 2270
Flash Point	207 °C	ASTM D 92
Pour point	-42 °C	ASTM D 97