



Eurol Fluid RFC

Residue-free vanishing stamping fluid

Description

Eurol Fluid RFC with Eurol SYNGIS Technology is an ashless, residue-free vanishing stamping fluid developed for medium-duty stamping and forming of metals. Eurol Fluid RFC offers corrosion protection during metalworking and does not need to be removed before further processing.

Eurol Fluid RFC is especially suitable for:

- Forming
- Stamping
- Bending
- Continuous metalworking processes
- Drum construction

Instructions for use

Remove old lubricant before applying
Apply a thin film by spraying, brushing or dipping
Remove any water with compressed air
Removing film before welding is not necessary

Eurol Fluid RFC has the following characteristics

Very good penetrating ability
Excellent emergency corrosion protection
Evaporates without leaving a residue
Effective water removal
Overpaintable without cleaning
Economical in use

Physical properties

Colour	Colourless		
Density at 20°C	0.794	kg/l	ASTM D 1298
Flash point	60	°C	ASTM D 93

Industrial oils - Metalworking - Article number S003500
Version 1.0, 19-07-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurolspecialty.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.