

specialty lubricants



Eurol Grease CS-2/103-S

Lubricating grease / anti-corrosion agent Article number S005109 Version 1.1 10/07/2025

Produktinformationen

Eurol Grease CS-2/103-S with a high dose of Eurol SYNGIS Technology is a high-performance grease developed for extreme situations such as in the paper, cement, and steel industries, and for heavy equipment in offshore and shipping.

Product benefits

- · Unique anti-wear and EP properties.
- Extreme protection against corrosion Shear stable.
- · Excellent water resistance.
- · Resistant to shock loading.
- · Very good thermal and oxidation stability.
- · Less oil bleeding, thus very suitable for automatic lubrication systems.
- Low friction coefficient Reduces energy consumption.
- · Economical in use.

Application

- · Open and closed bearings
- · Cables and chains
- Sliding parts
- Autoclaves
- · Steam valves
- · Agricultural and fishing equipment
- Equipment operating in extreme environments such as (salt) water and high temperatures.
- · Automatic lubrication systems

Instructions for use

· Thoroughly clean the system with Eurol Swift Clean 110 Spray.

Physical properties

Characteristic	Value/Result	ASTM Standard
Base oil viscosity	220 cSt	ASTM D 445
Color	brown	
Operating temperature	°C Min: -30 Max: 150 °C	
Thickener type	Syngis	
NLGI consistency	2	