



Eurol Grease CS-2/103-S

Lubrication grease / anti corrosion agent

Description

Eurol Grease CS-2/103-S with a high dose of Eurol SYNGIS Technology is a high performance lubricating grease developed for extreme situations in e.g. the paper, cement and steel industry and heavy equipment in offshore and shipping.

Eurol Grease CS-2/103-S is suitable for lubrication of:

- Open and closed bearings
- Cables and chains
- Autoclaves
- Steam valves
- Agricultural and fishing equipment
- Equipment working in extreme environments like (salt) water and high temperatures

Instructions for use

Clean the system thoroughly with Eurol Swift Clean 110 Spray
Suitable for automatic lubrication systems

Eurol Grease CS-2/103-S has the following characteristics

Unique anti wear and EP properties
Extreme protection against corrosion
Shear stable
Excellent water resistancy
Resistant to shock loads
Very good thermal and oxidation stability
Less oil bleeding, so very suitable for automatic lubrication systems
Low friction coefficient
Lowers energy consumption
Economical in use

Physical properties

Colour	brown	
NLGI consistency	2	ASTM D 217
Thickener type	Syngis	
Base oil viscosity	220 cSt	ASTM D 445
Operating temperature	-30 – 150 °C	

Greases - Article number S005109
Version 1.1, 09-08-2017

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurolspecialty.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.