



Eurol Grease CS-2/502-S Spray

Lubrication grease with dispersed SYNGIS additive

Description

Eurol Grease CS-2/502-S with Eurol SYNGIS Technology is a lubricating grease with a high viscosity base oil developed for low speed applications in e.g. the paper, cement and steel industry or for heavy equipment in offshore and shipping

This grease contains a high dose of SYNGIS additive, providing emergency lubrication when required.

Eurol Grease CS-2/502-S is suitable for lubrication of:

- Open and closed bearings
- Cables and chains
- Autoclaves
- Steam valves
- Agricultural and fishing equipment
- Equipment working in extreme environments like (salt) water and high temperatures

Instructions for use

Clean the system thoroughly with Eurol Swift Clean 110 Spray

Do not spray on a hot surface

Shake before use

Eurol Grease CS-2/502-S Spray has the following characteristics

High concentration dispersed SYNGIS additive

Excellent anti wear and EP properties

Extreme protection against corrosion

Shear stable

Excellent water resistancy

Resistant to shock loads

Oxidation stable

Less oil bleeding, so very suitable for automatic lubrication systems

Economical in use

Physical properties

Colour	brown		
NLGI consistency	2		ASTM D 217
Thickener type	Calcium Sulfonate		
Density at 20°C	0.9	kg/l	ASTM D 1298
Base oil type	Mineral		
Flash point	-20	°C	ASTM D 93
Operating temperature	-25 – 160	°C	