



POWERING
PERFORMANCE

PRODUCT DATA SHEET

specialty lubricants

Eurol Grease PU-2/502

High performance lubrication grease

Article number S005175 Version 1.0 16/04/2025

Product information

Eurol Grease PU-2/502 with Eurol SYNGIS Technology is a high-quality grease developed for extreme situations in the paper, cement, and steel industries.

Product benefits

- Excellent anti-wear properties
- Excellent corrosion protection
- Shear stable
- Oxidation stable
- Low friction coefficient
- Energy saving
- Economical in use

Application

- Open and closed bearings
- Equipment operating in extreme environments, such as a combination of water and temperatures up to 150°C

Usage instructions

- Thoroughly clean the system with Eurol Swift Clean 110 Spray.
- Never mix with other greases.

Performance level

- ISO-L-XBDIB 2/1

Physical properties

Characteristic	Value/Result	ASTM Standard
Color	brown	
Density at 20°C	0.90 kg/l	ASTM D 4052
Flash Point	200 °C	ASTM D 92
Base oil type	Mineral	
Thickener type	Polyurea	
NLGI consistency	2	

Eurol B.V., Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 88 250 22 00, info@eurol.com, eurol.com

This document is intended to inform you about the product features and possible applications of Eurol products. The information in this document is subject to change at any time without prior notice due to ongoing product research and development. The analysis data in this sheet contains typical values. Minor deviations, which can occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet has been compiled with great care, Eurol accepts no liability for damages resulting from any incompleteness and/or inaccuracies in the text. We always advise you to follow the manufacturer's instructions. The translations provided here are made using ChatGPT, an AI language model developed by OpenAI. While we strive to deliver accurate and useful translations, we cannot guarantee that all translations are error-free or always capture the correct context and nuances.