



Eurol Grease PL FD Spray

Multifunctional transparent grease with Eurol Syngis Technology

Description

Multipurpose transparent grease with Eurol Syngis Technology. Very suitable for the general grease lubrication of machines in the food industry where incidental food contact cannot be avoided. Provides anti corrosion properties and resists water, steam and alkaline cleaners. It has a long service life in wet areas and can be used to safely extend re-lubrication intervals. Thanks to the transparent nature of the grease, machine parts are easy to inspect.

Instructions for use

Clean and degrease parts thoroughly
Shake well before use
Apply a thin film
Allow the product to penetrate and dry
Remove excess product with a clean cloth
For more demanding applications Eurol Grease CS-2 / 102 FD Spray is a good alternative

Eurol Grease PL FD Spray has the following characteristics

NSF H1, 162327

Economical in use

Multifunctional grease for many applications
Contains Eurol Syngis Technology
Suitable for incidental food contact
Transparent so machine parts are easy to inspect
Colorless for clean lubrication
Resistant to water, steam and alkaline cleaners
Very good anti corrosion properties
Extends lubrication service intervals
Very low friction coefficient
Reduces energy consumption

Physical properties

Colour	Colourless	
NLGI consistency	2	ASTM D 217
Base oil viscosity	80 cSt	ASTM D 445
Base oil type	Pharmaceutical	
Operating temperature	-20 – 150 °C	