



Eurol Assembly Paste SG

High performance assembly paste with micronized SYNGIS additive

Description

Eurol Assembly Paste SG with Eurol SYNGIS Technology is an organic assembly paste developed for demanding situations in e.g. the paper, cement, fertilizer and salt industry.

Instructions for use

Clean the system thoroughly with Eurol Swift Clean 110 Spray
Apply a thin layer with a brush

Eurol Assembly Paste SG is suitable for treating and sealing of:

- Fittings
- Thread connections
- Elastomer seals
- Bearings

Eurol Assembly Paste SG has the following characteristics

Excellent protection against fretting corrosion

Extremely salt (sea)water resistant

Oxidation stable

Low friction coefficient

Economical in use

Free of microplastics

Physical properties

Colour	brown	
NLGI consistency	2	ASTM D 217
Density at 20°C	0.9 kg/l	ASTM D 1298
Base oil type	Mineral	
Operating temperature	-25 – 100 °C	

Greases - Article number S006100
Version 1.1, 18-06-2018

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurolspecialty.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.