



## Eurol Additive-S

Highly concentrated Syngis additive

### Description

Eurol Additive-S is a mix of carefully selected Eurol Syngis additives and has been developed for lubricating applications which are so heavily loaded that conventional lubrication is nearly impossible. It does not contain hazardous components such as chlorine and can effortlessly replace chlorinated paraffins. Eurol Additive-S can be added to an existing lubricant such as hydraulic oil, gearbox lubricant and even metalworking fluid, increasing EP performance spectacularly. It offers energy savings through a lower coefficient of friction.

As oil additive, Eurol Additive-S is highly suited for addition to:

- Extremely loaded gearboxes
- Hydraulic systems
- Exposed lubricating points such as couplings, exposed gears, bearings and hinges
- Very heavily loaded thread connections
- As drilling oil for heavy metalworking (on ferro metals)

### Eurol Additive-S has the following characteristics

Offers unparalleled extreme pressure properties  
Environmentally friendly and safe for use  
Reduces vibrations and noise  
Very low coefficient of friction  
Lowers energy consumption  
Extends drain intervals  
Does not contain chlorinated paraffin or phosphorus compounds  
Nearly odourless  
Economical in use

### Instructions for use

Shake well before use  
First replace highly contaminated oil and/or oil filters  
Add between 1% and 5% of additive to the new oil  
Contact your Eurol Specialty sales representative for a dedicated advice

### Physical properties

Colour	brown		
Density at 20°C	0.911	kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	21.9	cSt	ASTM D 445
Viscosity, kinematic at 100°C	5.5	cSt	ASTM D 445
Viscosity Index	207		ASTM D 2270
Flash point	60	°C	ASTM D 93
Pour point	-36	°C	ASTM D 97

Industrial oils - Article number S008300  
Version 1.0, 30-03-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, [www.eurolspecialty.com](http://www.eurolspecialty.com)

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.