



Eurol Additive-S Diesel

Diesel fuel additive for maintaining the entire fuel system

Description

Eurol Additive-S Diesel is a mix of specially selected Eurol Syngis additives. It has been developed as a diesel fuel additive for the maintenance of the entire fuel system and works preventively against corrosion and condensation in the fuel tank and fuel lines. This product also replaces an injection cleaner, which is commonly used together with a system cleaner. Use is recommended to remove and prevent diesel engine pollution. Eurol Additive-S Diesel ensures a smoothly operating diesel engine, a better start, less emissions, lower fuel consumption and more power. It does not contain chlorine.

Instructions for use

First replace heavily polluted fuel filters
1000ml Eurol Additive-S Diesel is suitable for 1000L of diesel fuel
Add before refuelling to ensure a homogeneous mixture of additive and fuel
Let the additive circulate through the system to enable proper functioning
Repeat every 2 to 3 fuel refills

Eurol Additive-S Diesel has the following characteristics

For heavily loaded diesel engines in e.g. earthmoving equipment, ships and generators
Environmentally friendly and safe in use
Reduces vibrations and noise
Reduces fuel consumption
Increases power output
Free from chlorinated paraffins
Economical in use

Physical properties

Colour	Yellow		
Density at 20°C	0.945	kg/l	ASTM D 1298
Flash point	76	°C	ASTM D 93
Pour point	-39	°C	ASTM D 97