



## Eurol Lube PL Spray

“Dry” multi-functional lubricant reinforced with SYNGIS Technology

### Description

Eurol Lube PL Spray is a “dry” lubricant with Eurol SYNGIS Technology. Eurol Lube PL Spray has been developed for non-drip, “dry”, clean and durable lubrication of many applications where excellent creeping, penetration and anti-corrosion properties are required. It displaces moisture, resists water and loosens corroded parts. Thanks to the “dry” lubrication properties dirt and sand are not being picked up.

Eurol Lube PL Spray is especially suitable for:

- All open lubrication points like e.g. joints, bearings and hinges
- Cables and conveyors

### Instructions for use

Clean and degrease parts thoroughly  
Shake well before use  
Apply a thin film  
Allow the product to penetrate and dry  
Remove excess product with a clean cloth  
For more demanding applications, Eurol CL-F Lube with a higher concentration SYNGIS Technology is available

### Eurol Lube PL Spray has the following characteristics

Excellent anti wear properties  
Excellent protection against corrosion  
Excellent cleaning action  
Outstanding water repellency  
Very good creeping and penetration properties  
Loosens corroded parts  
Gives a thin and “dry” protective lubrication film  
Does not attract dirt or sand  
Very low friction coefficient  
Reduces energy consumption  
Economical in use

### Physical properties

Colour	Yellow		
Density at 20°C	0.937	kg/l	ASTM D 1298
Viscosity Index	193		ASTM D 2270
Operating temperature	-40 – 170	°C	