



Eurol Lube PL

“Dry” multi-functional lubricant reinforced with SYNGIS Technology

Description

Eurol Lube PL is a “dry” lubricant with Eurol SYNGIS Technology. Eurol Lube PL has been developed for non-drip, “dry”, clean and durable lubrication of many applications where excellent creeping, penetration and anti-corrosion properties are required. It displaces moisture, resists water and loosens corroded parts. Thanks to the “dry” lubrication properties dirt and sand are not being picked up.

Eurol Lube PL is especially suitable for:

- All open lubrication points like e.g. joints, bearings and hinges
- Cables and conveyors

Instructions for use

Clean and degrease parts thoroughly

Apply a thin film

Allow the product to penetrate and dry

Remove excess product with a clean cloth

For more demanding applications, Eurol CL-F Lube with a higher concentration SYNGIS Technology is available

Eurol Lube PL has the following characteristics

Excellent anti wear properties

Excellent protection against corrosion

Excellent cleaning action

Outstanding water repellency

Very good creeping and penetration properties

Loosens corroded parts

Gives a thin and “dry” protective lubrication film

Does not attract dirt or sand

Very low friction coefficient

Reduces energy consumption

Economical in use

Physical properties

Colour	brown		
Density at 20°C	0.872	kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	32	cSt	ASTM D 445
Viscosity, kinematic at 100°C	9.1	cSt	ASTM D 445
Viscosity Index	287		ASTM D 2270
Flash point	60	°C	ASTM D 93
Pour point	-42	°C	ASTM D 97
Operating temperature	-20 – 140	°C	

Industrial oils - Semi-synthetic - Article number S009101
Version 1.2, 08-05-2023

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurolspecialty.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.