



Eurol Lube PL Spray

“Dry” multi-functional lubricant reinforced with SYNGIS Technology

Description

Eurol Lube PL Spray is a “dry” lubricant with Eurol SYNGIS Technology. Eurol Lube PL Spray has been developed for non-drip, “dry”, clean and durable lubrication of many applications where excellent creeping, penetration and anti-corrosion properties are required. It displaces moisture, resists water and loosens corroded parts. Thanks to the “dry” lubrication properties dirt and sand are not being picked up.

Eurol Lube PL Spray is especially suitable for:

- All open lubrication points like e.g. joints, bearings and hinges
- Cables and conveyors

Instructions for use

Clean and degrease parts thoroughly

Shake well before use

Apply a thin film

Allow the product to penetrate and dry

Remove excess product with a clean cloth

For more demanding applications, Eurol CL-F Lube with a higher concentration Syngis Technology is available

Eurol Lube PL Spray has the following characteristics

Excellent anti wear properties

Excellent protection against corrosion

Excellent cleaning action

Outstanding water repellency

Very good creeping and penetration properties

Loosens corroded parts

Gives a thin and “dry” protective lubrication film

Does not attract dirt or sand

Very low friction coefficient

Reduces energy consumption

Economical in use

Physical properties

Colour	Yellow		
Density at 20°C	0.937	kg/l	ASTM D 1298
Viscosity Index	193		ASTM D 2270
Operating temperature	-40 – 170	°C	