

specialty lubricants SYN



Eurol Lube PL FD

"Dry" multi-functional foodgrade lubricant reinforced with SYNGIS Technology

Description

Eurol Lube PL FD is a "dry" lubricant with Eurol SYNGIS Technology for applications in the food industry. Eurol Lube PL FD has been developed for non-drip, "dry", clean and durable lubrication of many applications where excellent creeping, penetration and anti-corrosion properties are required. It displaces moisture, resists water and loosens corroded parts. Thanks to the "dry" lubrication properties dirt and sand are not being picked up.

Eurol Lube PL FD is especially suitable for:

- · All open lubrication points like e.g. joints, bearings and hinges
- · Chains, cables and conveyors
- · Linear guides

Instructions for use

Clean and degrease parts thoroughly using Eurol Swift Clean 120 FD Spray Apply a thin film Allow the product to penetrate and dry Remove excess product with a clean cloth

Eurol Lube PL FD has the following characteristics

NSF H1, 163577 Economical in use

Excellent anti wear properties

Excellent protection against corrosion

Excellent cleaning action

Outstanding water repellency

Very good creeping and penetration properties

Loosens corroded parts

Gives a thin and "dry" protective lubrication film

Does not attract dirt or sand

Very low friction coefficient

Reduces energy consumption

Physical properties

Colour	brown		
Density at 20°C	0.875	kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	55.5	cSt	ASTM D 445

Industrial oils - Food - Article number S009120 Version 1.2, 28-06-2023