



Eurol Lube PL BIO

Biodegradable lubricant reinforced with SYNGIS Technology

Description

Eurol Lube PL BIO is a "dry" lubricant with Eurol SYNGIS Technology. Eurol Lube PL BIO has been developed for non-drip, clean and durable lubrication of many applications where excellent creeping, penetration and anti-corrosion properties are required. It displaces moisture, resists water and loosens corroded parts. Thanks to the "dry" lubrication properties, dirt and sand are not being picked up. Eurol Lube PL BIO is especially developed to protect against extreme pressure and wear.

Eurol Lube PL BIO is especially suitable for open lubrication points like e.g. joints, bearings, hinges and cables.

Eurol Lube PL BIO contains partly bio-derived lubricant and is readily biodegradable.

Instructions for use

Clean and degrease parts thoroughly
Apply a thin film
Allow the product to penetrate and dry
Remove excess product with a clean cloth

Eurol Lube PL BIO has the following characteristics

- Partly bio-derived lubricant
- Readily biodegradable lubricant
- Excellent anti wear properties
- Excellent protection against corrosion
- Good water repellency
- Loosens corroded parts
- Gives a thin and "dry" protective lubrication film
- Does not attract dirt or sand
- Very low friction coefficient
- Suitable for use in refillable aerosol

Physical properties

Colour	Yellow		
Density at 20°C	0.918	kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	36	cSt	ASTM D 445
Viscosity, kinematic at 100°C	7.6	cSt	ASTM D 445
Viscosity Index	187		ASTM D 2270
Flash point	150	°C	ASTM D 93
Pour point	-21	°C	ASTM D 97

Industrial oils - Bio - Article number S009125
Version 1.0, 23-05-2023

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurolspecialty.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.