



Eurol Specialty Racing ATF

High performance automatic transmission fluid for racing applications

Description

Eurol Specialty Racing ATF is a fully synthetic racing automatic transmission fluid based on Eurol SYNGIS Technology. This additive technology ensures high power output and unmatched protection against wear in the most extreme conditions.

Developed for competition use. It has been approved for use in automatic transmissions, torque converters and power steering systems. Eurol Specialty Racing ATF has been successfully used in:

- Beast 2020 – Coronel Dakar team
 - Riwald Renault C460 Hybrid – MKR Technology
- Approved and recommended by MKR Technology

Instructions for use

Flush the transmission or torque converter using Eurol Additive-S Flush in the old transmission fluid.

Drain the old oil and change the filter if present.

Note: Eurol Specialty Racing ATF is not recommended for street use. In case of any application-related questions, please visit www.eurol.com/racing

Eurol Specialty Racing ATF has the following characteristics

Outstanding detergency, excellent transmission cleanliness

Reduces friction, lowers gearbox temperature and increases top speed

Virtually no viscosity loss during use, extending gearbox life

Physical properties

Colour	red		
Density at 20°C	0.854	kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	57.2	cSt	ASTM D 445
Viscosity, kinematic at 100°C	10	cSt	ASTM D 445
Viscosity Index	172		ASTM D 2270
Flash point	174	°C	ASTM D 93
Pour point	-39	°C	ASTM D 97